

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
Tên nhóm: 1									
KQSN150-M4-310	96	127	65	2960	310	90	DN100	DN150	545 kg
	160	120	73						
	202	108	72						
KQSN150-M4-295	91	114	93	2960	295	75	DN100	DN150	505 kg
	152	108	72						
	192	97	70						
KQSN150-M4-276	85	100	61	2960	276	75	DN100	DN150	505 kg
	142	95	71						
	180	86	68						
KQSN150-M4-257	80	87	59	2960	257	55	DN100	DN150	477 kg
	131	83	70						
	169	74	66						
KQSN150-N4-310	131	116	73	2960	310	75	DN100	DN150	505 kg
	171	106	71						
	811	123	59						
KQSN150-N4-295	77	111	57	2960	295	75	DN100	DN150	505 kg
	124	105	72						
	163	96	69						
KQSN150-N4-276	72	97	55	2960	276	55	DN100	DN150	477 kg
	117	92	71						
	153	84	67						
KQSN150-N4-257	68	85	53	2960	257	45	DN100	DN150	365 kg
	109	80	70						
	142	73	65						
KQSN150-M6-245	101	90	66	2960	245	55	DN100	DN150	477 kg
	168	83	79						
	202	75	76						
KQSN150-M6-225	88	75	64	2960	225	45	DN100	DN150	365 kg
	155	70	78						
	182	60	74						
KQSN150-M6-211	89	66	62	2960	211	37	DN100	DN150	311 kg
	144	61	77						
	183	52	72						
KQSN150-M6-201	90	60	60	2960	201	37	DN100	DN150	311 kg
	138	56	76						
	184	47	70						
KQSN150-N6-245	87	87	59	2960	245	45	DN100	DN150	365 kg
	145	78	80						
	174	74	77						
KQSN150-N6-228	81	75	57	2960	228	37	DN100	DN150	311 kg
	135	67	79						
	162	64	76						
KQSN150-N6-208	74	63	55	2960	208	30	DN100	DN150	293 kg
	123	56	78						
	148	53	74						
KQSN150-N6-201	71	59	53	2960	201	30	DN100	DN150	293 kg
	119	52	77						
	143	49	72						
KQSN150-M7-332	234	146	76	2960	332	200	DN100	DN150	1219 kg
	390	132	82						
	468	108	79						
KQSN150-M7-318	224	135	76	2960	318	185	DN100	DN150	1219 kg
	374	121	81						
	448	98	78						
KQSN150-M7-305	215	120	73	2960	305	160	DN100	DN150	1141 kg
	358	111	80						
	430	85	77						
KQSN150-M7-283	199	104	74	2960	283	132	DN100	DN150	1094 kg
	332	96	79						
	399	74	78						
KQSN150-M7-260	183	88	75	2960	260	110	DN100	DN150	1001 kg
	305	81	78						
	367	64	77						
KQSN150-N7-332	171	137	77	2960	332	132	DN100	DN150	1094 kg
	285	120	84,5						
	342	105	80						
KQSN150-N7-305	159	118	81	2960	305	110	DN100	DN150	1001 kg
	265	103	83,5						
	318	89	82						
KQSN150-N7-283	150	99	80	2960	283	90	DN100	DN150	545 kg
	250	84	82,5						
	300	74	81						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN150-N7-260		140	81	79	2960	260	75	DN100	DN150	505 kg
		234	69	81,5						
		281	59	80						
Tên nhóm: 2										
KQSN200-M4-388		168	200	63	2960	388	250	DN125	DN200	268 kg
		280	193	70						
		336	180	67						
KQSN200-M4-360		155	176	61	2960	360	220	DN125	DN200	1619 kg
		258	165	69						
		310	155	67						
KQSN200-M4-328		142	146	59	2960	328	160	DN125	DN200	1141 kg
		236	138	68						
		284	132	65						
KQSN200-M4-305		132	131	58	2960	305	132	DN125	DN200	1094 kg
		220	120	67						
		250	112	64						
KQSN200-M4-283		124	113	57	2960	283	110	DN125	DN200	1001 kg
		207	103	66						
		245	101	63						
KQSN200-N4-388		143	196	62	2960	388	220	DN125	DN200	1619 kg
		238	190	70						
		285	176	66						
KQSN200-N4-360		124	172	60	2960	360	160	DN125	DN200	1141 kg
		208	160	69						
		250	151	65						
KQSN200-N4-328		156	136	58	2960	328	132	DN125	DN200	1094 kg
		196	133	68						
		236	127	63						
KQSN200-N4-286		114	109	56	2960	286	110	DN125	DN200	1001 kg
		190	102	67						
		221	98	61						
KQSN200-M5-420		264	232	68	2960	420	450	DN125	DN200	3290 kg
		440	225	82						
		528	220	77						
KQSN200-M5-398		250	208	67	2960	398	400	DN125	DN200	3290 kg
		416	201	81,5						
		499	196	76						
KQSN200-M5-378		234	182	66	2960	378	315	DN125	DN200	1980 kg
		390	177	81						
		468	173	75						
KQSN200-M5-355		221	163	65	2960	355	280	DN125	DN200	1812 kg
		368	157	80,5						
		442	154	71						
KQSN200-M5-336		207	143	64	2960	336	250	DN125	DN200	1717 kg
		345	138	80						
		414	135	73						
KQSN200-N5-418		225	216	64	2960	418	355	DN125	DN200	2850 kg
		375	210	78						
		450	206	73						
KQSN200-N5-396		214	195	63	2960	396	315	DN125	DN200	1980 kg
		356	189	77						
		427	185	72						
KQSN200-N5-375		203	176	62	2960	375	280	DN125	DN200	1812 kg
		338	171	76						
		406	168	71						
KQSN200-N5-352		193	159	61	2960	352	250	DN125	DN200	1717 kg
		321	154	75						
		385	151	70						
KQSN200-N5-334		183	143	60	2960	334	220	DN125	DN200	1619 kg
		305	139	74						
		366	136	69						
KQSN200-M6-280		168	105	64	2960	280	132	DN150	DN200	1094 kg
		280	95	83						
		326	85	78						
KQSN200-M6-274		163	98	62	2960	274	110	DN150	DN200	1001 kg
		272	90	82						
		326	80	76						
KQSN200-M6-258		154	87	60	2960	258	90	DN150	DN200	545 kg
		256	80	81						
		307	71	74						
KQSN200-M6-237		141	74	58	2960	237	75	DN150	DN200	505 kg
		235	67	80						
		282	60	72						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN200-N6-280	143	102	58	2960	280	90	DN150	DN200	545 kg
	238	92	79						
	285	83	77						
KQSN200-N6-258	131	86	56	2960	258	75	DN150	DN200	505 kg
	219	78	78						
	262	70	75						
KQSN200-N6-244	124	77	54	2960	244	75	DN150	DN200	505 kg
	207	70	78						
	248	63	73						
KQSN200-N6-237	120	72	52	2960	237	55	DN150	DN200	477 kg
	200	64	77						
	239	57	67						
KQSN200-M7-340	175	39	70	1480	340	45	DN150	DN200	375 kg
	250	36	81						
	313	32	76						
KQSN200-M7-321	165	35	69	1480	321	45	DN150	DN200	255 kg
	236	32	80						
	295	28	74						
KQSN200-M7-300	154	30	68	1480	300	30	DN150	DN200	298 kg
	220	28	79						
	276	25	73						
KQSN200-M7-278	143	26	67	1480	278	22	DN150	DN200	233 kg
	204	24	78						
	255	21	72						
KQSN200-M7-253	130	22	65	1480	253	18.5	DN150	DN200	222 kg
	186	20	76						
	233	18	70						
KQSN200-N7-340	147	37	69	1480	340	30	DN150	DN200	298 kg
	209	34	80						
	262	30	74						
KQSN200-N7-321	138	32	68	1480	321	30	DN150	DN200	298 kg
	197	30	79						
	246	26	73						
KQSN200-N7-300	128	28	67	1480	300	22	DN150	DN200	233 kg
	183	26	78						
	229	23	72						
KQSN200-N7-278	101	24	65	1480	278	18.5	DN150	DN200	222 kg
	168	22	75						
	211	19	69						
KQSN200-N7-253	107	19	65	1480	253	15	DN150	DN200	222 kg
	152	18	75						
	190	16	69						
KQSN200-M8-305	318	125	75	2960	305	220	DN125	DN200	1619 kg
	530	111	84						
	636	95	81,5						
KQSN200-M8-292	305	115	74	2960	292	185	DN125	DN200	1141 kg
	508	100	83						
	609	87	81						
KQSN200-M8-278	291	105	74	2960	278	160	DN125	DN200	1141 kg
	485	88	82						
	582	78	80,5						
KQSN200-M8-256	263	89	73	2960	256	132	DN125	DN200	1094 kg
	439	72	81						
	527	63	78						
KQSN200-M8-235	235	73	72	2960	235	110	DN125	DN200	1001 kg
	392	57	80						
	470	50	77						
KQSN200-N8-305	288	121	75	2960	305	185	DN125	DN200	1141 kg
	480	100	83						
	576	85	80						
KQSN200-N8-278	263	100	74	2960	278	160	DN125	DN200	1141 kg
	439	84	82						
	527	70	79						
KQSN200-N8-256	241	83	73	2960	256	110	DN125	DN200	1001 kg
	401	70	81						
	481	57	76						
KQSN200-N8-235	214	66	72	2960	235	90	DN125	DN200	1001 kg
	356	55	80						
	427	44	74						
KQSN200-M9-235	168	73	74	2960	235	75	DN150	DN200	505 kg
	300	66	84						
	351	51	78						
	160	65	72						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN200-M9-223		285	58	83	2960	223	75	DN150	DN200	505 kg
		333	45	75						
KQSN200-M9-212		151	59	70	2960	212	55	DN150	DN200	477 kg
		270	52	82						
		316	41	73	2960	200	45	DN150	DN200	365 kg
	KQSN200-M9-200	143	52	68						
		255	47	81	2960	235	75	DN150	DN200	505 kg
	KQSN200-N9-235	298	36	71						
		143	71	66	2960	228	55	DN150	DN200	477 kg
	KQSN200-N9-228	238	62	83						
		298	50	76	2960	212	45	DN150	DN200	365 kg
	KQSN200-N9-212	128	57	62						
		214	50	79	2960	198	37	DN150	DN200	295 kg
	KQSN200-N9-198	268	40	72						
		121	51	60	2960	246	132	DN150	DN200	1094 kg
	KQSN200-M12-246	202	44	77						
		240	35	70	2960	228	110	DN150	DN200	1001 kg
	KQSN200-M12-228	320	75	76						
		534	61	85,5	2960	211	75	DN150	DN200	505 kg
	KQSN200-M12-211	641	50	82						
		298	65	75	2960	195	75	DN150	DN200	505 kg
	KQSN200-M12-195	497	53	84						
		596	43	81	2960	246	110	DN150	DN200	1001 kg
	KQSN200-N12-246	272	56	73						
		454	44	82,5	2960	228	90	DN150	DN200	545 kg
	KQSN200-N12-228	545	34	78						
		255	46	71	2960	211	75	DN150	DN200	505 kg
	KQSN200-N12-211	425	35	81						
		510	29	74	2960	195	55	DN150	DN200	477 kg
	KQSN200-N12-195	284	77	76						
		473	61	84,5	2960	531	160	DN150	DN250	1192 kg
	KQSN200-N12-195	568	51	82						
		266	67	74	2960	497	132	DN150	DN250	1192 kg
	KQSN200-N12-497	443	54	84						
		532	43	81	2960	473	132	DN150	DN250	1192 kg
	KQSN200-N12-473	246	57	73						
		410	45	82	2960	595	200	DN150	DN250	1764 kg
	KQSN200-N4-595	492	37	79						
		229	48	71	2960	565	185	DN150	DN250	1281 kg
	KQSN200-N4-565	381	37	81						
		457	30	78	2960	531	160	DN150	DN250	1192 kg
	KQSN200-N4-531	217	79	73						
		362	75	81	2960	497	132	DN150	DN250	1192 kg
	KQSN200-N4-497	434	69	76						
		207	72	72	2960	497	132	DN150	DN250	1192 kg
	KQSN200-N4-497	207	72	72						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN250-N4-475		346	68	80	1480	475	110	DN150	DN250	1192 kg
		415	63	75						
KQSN250-M6-473		302	84	71	1480	473	185	DN150	DN250	1192 kg
		493	75	80						
KQSN250-M6-447		631	67	75	1480	447	160	DN150	DN250	1192 kg
		291	77	72						
KQSN250-M6-437		485	66	79	1480	437	132	DN150	DN250	1192 kg
		612	59	73						
KQSN250-M6-410		282	72	71	1480	410	110	DN150	DN250	1018 kg
		470	64	78						
KQSN250-M6-383		594	55	74	1480	383	90	DN150	DN250	615 kg
		265	63	69						
KQSN250-M6-356		441	56	77	1480	356	75	DN150	DN250	550 kg
		550	48	72						
KQSN250-N6-473		247	55	67	1480	473	160	DN150	DN250	1192 kg
		412	49	76						
KQSN250-N6-447		520	42	71	1480	447	110	DN150	DN250	1192 kg
		230	47	66						
KQSN250-N6-428		383	42	75	1480	428	110	DN150	DN250	1018 kg
		483	36	70						
KQSN250-N6-410		258	83	66	1480	410	90	DN150	DN250	615 kg
		432	75	80						
KQSN250-N6-383		535	67	73	1480	383	75	DN150	DN250	550 kg
		252	75	67						
KQSN250-N6-356		420	64	79	1480	356	75	DN150	DN250	550 kg
		520	57	74						
KQSN250-M9-367		239	67	65	1480	367	75	DN200	DN250	550 kg
		399	59	78						
KQSN250-M9-349		504	52	72	1480	349	75	DN200	DN250	550 kg
		229	62	63						
KQSN250-M9-327		382	54	77	1480	327	55	DN200	DN250	494 kg
		482	48	71						
KQSN250-M9-300		214	54	61	1480	300	45	DN200	DN250	375 kg
		357	47	76						
KQSN250-N9-367		451	42	70	1480	367	75	DN200	DN250	550 kg
		199	47	59						
KQSN250-N9-341		332	41	75	1480	341	55	DN200	DN250	494 kg
		419	36	69						
KQSN250-N9-316		291	46	72	1480	316	45	DN200	DN250	375 kg
		485	41	83						
KQSN250-N9-300		612	34	79	1480	300	37	DN200	DN250	350 kg
		276	41	70						
KQSN300-M3-816		461	37	81	1480	816	800	DN200	DN300	4600 kg
		581	30	77						
KQSN300-M3-780		259	23	68	1480	780	710	DN200	DN300	4550 kg
		432	32	79						
KQSN300-M3-738		545	25	76	1480	738	630	DN200	DN300	3461 kg
		242	18	66						
		403	27	77						
		490	20	75						
		247	13	65						
		412	39	83						
		519	34	78						
		230	38	63						
		383	34	81						
		483	29	78						
		212	33	61						
		354	29	79						
		447	25	74						
		205	30	59						
		342	25	77						
		415	21	72						
Tên nhóm: 4										
KQSN300-M3-816		474	225	61	1480	816	800	DN200	DN300	4600 kg
		790	220	70						
KQSN300-M3-780		909	215	67	1480	780	710	DN200	DN300	4550 kg
		459	205	60						
KQSN300-M3-738		765	200	69	1480	738	630	DN200	DN300	3461 kg
		880	195	66						
		442	186	59						
		736	180	68						
		846	174	65						
		424	166	58						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN300-M3-685	707	160	67	1480	685	560	DN200	DN300	3380 kg
	813	153	64						
KQSN300-N3-816	402	214	60	1480	816	710	DN200	DN300	4550 kg
	670	210	68						
KQSN300-N3-780	777	205	65	1480	780	630	DN200	DN300	3461 kg
	388	194	59						
KQSN300-N3-738	647	190	67	1480	738	560	DN200	DN300	3380 kg
	751	185	64						
KQSN300-N3-685	375	175	58	1480	685	500	DN200	DN300	3315 kg
	625	170	66						
KQSN300-M4-690	731	165	63	1480	690	560	DN200	DN300	2520 kg
	361	156	57						
KQSN300-M4-665	602	150	65	1480	665	500	DN200	DN300	1870 kg
	710	144	62						
KQSN300-M4-652	504	163	76	1480	652	450	DN200	DN300	3315 kg
	840	160	84						
KQSN300-M4-618	1008	152	82	1480	618	400	DN200	DN300	3200 kg
	484	152	75						
KQSN300-M4-592	806	147	83	1480	592	355	DN200	DN300	3290 kg
	968	140	81						
KQSN300-M4-559	464	140	74	1480	559	315	DN200	DN300	2900 kg
	774	136	82						
KQSN300-N4-690	929	132	80	1480	690	450	DN200	DN300	3315 kg
	446	129	73						
KQSN300-N4-665	743	125	81	1480	665	355	DN200	DN300	3100 kg
	892	118	79						
KQSN300-N4-638	428	120	72	1480	638	315	DN200	DN300	2200 kg
	713	115	80						
KQSN300-N4-612	856	108	78	1480	612	280	DN200	DN300	2084 kg
	411	109	71						
KQSN300-N4-585	685	106	79	1480	585	250	DN200	DN300	1947 kg
	822	103	77						
KQSN300-N4-559	414	150	70	1480	559	220	DN200	DN300	1764 kg
	690	144	84						
KQSN300-M6-530	828	139	76	1480	530	315	DN200	DN300	2084 kg
	397	142	68						
KQSN300-M6-509	662	133	83	1480	509	280	DN200	DN300	1947 kg
	795	128	80						
KQSN300-M6-482	382	131	68	1480	482	250	DN200	DN300	1764 kg
	636	122	83						
KQSN300-M6-456	763	117	80	1480	456	220	DN200	DN300	1705 kg
	366	122	67						
KQSN300-N6-530	610	113	82	1480	443	200	DN200	DN300	1281 kg
	733	108	79						
KQSN300-N6-509	352	111	66	1480	443	200	DN200	DN300	1281 kg
	586	104	81						
KQSN300-N6-488	703	99	78	1480	488	220	DN200	DN300	1705 kg
	338	102	65						
KQSN300-N6-443	563	96	80	1480	443	200	DN200	DN300	1281 kg
	675	91	77						
KQSN300-N6-408	474	98	74	1480	408	220	DN200	DN300	1705 kg
	800	94	84						
KQSN300-N6-370	948	86	80	1480	370	220	DN200	DN300	1705 kg
	455	91	71						
KQSN300-N6-337	758	86	81	1480	337	220	DN200	DN300	1705 kg
	910	79	77						
KQSN300-N6-304	431	82	68	1480	304	220	DN200	DN300	1705 kg
	719	78	78						
KQSN300-N6-271	863	71	74	1480	271	220	DN200	DN300	1705 kg
	408	73	66						
KQSN300-N6-238	679	69	76	1480	238	220	DN200	DN300	1705 kg
	815	63	72						
KQSN300-N6-205	398	70	63	1480	205	220	DN200	DN300	1705 kg
	664	65	73						
KQSN300-N6-172	790	58	68	1480	172	220	DN200	DN300	1705 kg
	402	95	67						
KQSN300-N6-139	670	91	84	1480	139	220	DN200	DN300	1705 kg
	804	83	79						
KQSN300-N6-106	386	87	65	1480	106	220	DN200	DN300	1705 kg
	644	84	82						
KQSN300-N6-73	772	76	77	1480	73	220	DN200	DN300	1705 kg
	370	80	62						
KQSN300-N6-40	617	77	79	1480	40	220	DN200	DN300	1705 kg
	617	77	79						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN300-N6-445	740	70	74	1480	445	185	DN200	DN300	1281 kg
	338	67	59						
	563	64	76						
	676	59	71						
KQSN300-M6W-654	810	148	67	1480	654	710	DN200	DN300	4700 kg
	1350	126	85						
	1620	106	74						
KQSN300-M6W-634	786	139	66	1480	634	630	DN200	DN300	4700 kg
	1310	120	84						
	1571	98	73						
KQSN300-M6W-608	762	128	65	1480	608	560	DN200	DN300	4700 kg
	1270	110	82						
	1524	90	72						
KQSN300-M6W-583	739	117	64	1480	583	500	DN200	DN300	4185 kg
	1232	103	81						
	1479	83	71						
KQSN300-M6W-543	717	102	62	1480	543	450	DN200	DN300	4185 kg
	1196	88	78						
	1434	72	69						
KQSN300-M6W-531	696	97	61	1480	531	400	DN200	DN300	4185 kg
	1159	85	77						
	1391	68	68						
KQSN300-M6WJ-654	542	65	67	990	654	200	DN200	DN300	1779 kg
	903	56	85						
	1084	48	74						
KQSN300-M6WJ-634	525	61	66	990	634	185	DN200	DN300	1685 kg
	875	53	84						
	1051	45	73						
KQSN300-M6WJ-608	504	56	65	990	608	160	DN200	DN300	1645 kg
	840	49	82						
	1007	41	72						
KQSN300-M6WJ-583	483	52	64	990	583	132	DN200	DN300	1239 kg
	805	45	81						
	966	35	71						
KQSN300-M6WJ-543	450	45	62	990	543	132	DN200	DN300	1239 kg
	750	39	78						
	900	33	69						
KQSN300-M6WJ-531	440	43	61	990	531	110	DN200	DN300	1211 kg
	733	37	77						
	879	31	68						
KQSN300-M9-445	474	68	74	1480	445	185	DN250	DN300	1282 kg
	790	61	88						
	972	53	84						
KQSN300-M9-423	450	61	72	1480	423	160	DN250	DN300	1192 kg
	751	55	86						
	923	47	82						
KQSN300-M9-387	412	51	70	1480	387	132	DN250	DN300	1192 kg
	687	46	84						
	846	39	80						
KQSN300-M9-356	379	43	68	1480	356	110	DN250	DN300	1018 kg
	632	39	82						
	778	33	78						
KQSN300-N9-445	402	66	64	1480	445	160	DN250	DN300	1192 kg
	670	59	85						
	825	52	80						
KQSN300-N9-418	378	58	62	1480	418	132	DN250	DN300	1192 kg
	630	52	83						
	775	46	78						
KQSN300-N9-392	354	51	60	1480	392	110	DN250	DN300	1018 kg
	590	46	81						
	726	40	76						
KQSN300-N9-356	322	42	58	1480	356	90	DN250	DN300	615 kg
	536	38	79						
	660	33	74						
KQSN300-M9W-503	756	86	70	1480	503	355	DN200	DN300	2900 kg
	1260	77	87						
	1512	68	81						
KQSN300-M9W-473	711	77	69	1480	473	315	DN200	DN300	2084 kg
	1184	69	86						
	1421	61	80						
KQSN300-M9W-453	680	71	68	1480	453	280	DN200	DN300	1947 kg
	1134	63	85						
	1361	55	79						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN300-M9W-433	650	62	67	1480	433	250	DN200	DN300	1764 kg
	1084	58	84						
	1300	52	78						
KQSN300-M9W-415	624	57	66	1480	415	220	DN200	DN300	1705 kg
	1040	53	83						
	1247	46	77						
KQSN300-M9WJ-503	506	40	70	990	503	110	DN200	DN300	1211 kg
	843	34	87						
	1011	29	81						
KQSN300-M9WJ-473	475	35	69	990	473	90	DN200	DN300	1120 kg
	792	30	86						
	951	26	80						
KQSN300-M9WJ-453	455	32	68	990	453	75	DN200	DN300	954 kg
	759	28	85						
	910	24	79						
KQSN300-M9WJ-433	435	29	67	990	433	75	DN200	DN300	954 kg
	725	25	84						
	870	22	78						
KQSN300-M9WJ-415	417	27	66	990	415	75	DN200	DN300	954 kg
	695	23	83						
	834	20	77						
KQSN300-M13-348	474	40	72	1480	348	110	DN250	DN300	1018 kg
	790	34	88						
	948	28	83						
KQSN300-M13-331	450	36	71	1480	331	90	DN250	DN300	615 kg
	751	30	87						
	901	25	82						
KQSN300-M13-313	427	32	70	1480	313	75	DN250	DN300	550 kg
	711	27	86						
	853	22	81						
KQSN300-M13-289	393	27	69	1480	289	55	DN250	DN300	494 kg
	656	23	85						
	787	19	80						
KQSN300-N13-348	402	38	65	1480	348	90	DN250	DN300	615 kg
	670	33	88						
	804	27	82						
KQSN300-N13-334	386	35	64	1480	334	75	DN250	DN300	550 kg
	644	30	87						
	772	25	81						
KQSN300-N13-303	350	29	63	1480	303	55	DN250	DN300	494 kg
	583	25	86						
	700	20	80						
KQSN300-N13-289	334	26	62	1480	289	55	DN250	DN300	494 kg
	556	23	85						
	668	19	79						
KQSN300-M13W-406	756	54	75	1480	406	220	DN250	DN300	1705 kg
	1260	46	88						
	1512	38	80						
KQSN300-M13W-390	726	50	74	1480	390	185	DN250	DN300	1582 kg
	1210	42	86,5						
	1452	34	79						
KQSN300-M13W-357	665	42	72	1480	357	160	DN250	DN300	1582 kg
	1109	35	84						
	1331	28	77						
KQSN300-M13W-333	620	36	70	1480	333	132	DN250	DN300	1192 kg
	1033	31	83						
	1240	25	75						
KQSN300-M13WJ-406	506	24	75	990	406	75	DN250	DN300	954 kg
	843	21	88						
	1011	17	80						
KQSN300-M13WJ-390	485	22	74	990	390	55	DN250	DN300	530 kg
	809	19	86,5						
	971	16	79						
KQSN300-M13WJ-357	445	18	72	990	357	45	DN250	DN300	495 kg
	742	16	84						
	890	14	77						
KQSN300-M13WJ-333	415	16	70	990	333	37	DN250	DN300	470 kg
	691	14	83						
	829	12	75						
KQSN300-M19-285	474	24	78	1480	285	55	DN250	DN300	494 kg
	790	20	88						
	948	14	81						
	450	22	75						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN300-M19-271	751	18	85	1480	271	55	DN250	DN300	494 kg
	901	12	78						
KQSN300-M19-257	427	19	72	1480	257	45	DN250	DN300	375 kg
	711	16	82						
KQSN300-M19-242	853	11	75	1480	242	37	DN250	DN300	350 kg
	403	17	69						
KQSN300-N19-285	672	14	79	1480	285	45	DN250	DN300	375 kg
	806	10	72						
KQSN300-N19-270	402	23	70	1480	270	37	DN250	DN300	350 kg
	670	19	88						
KQSN300-N19-254	804	13	80	1480	254	37	DN250	DN300	350 kg
	382	20	67						
KQSN300-N19-242	637	16	85	1480	242	37	DN250	DN300	350 kg
	764	12	77						
KQSN300-M27-251	358	18	64	1480	251	37	DN300	DN300	350 kg
	597	15	82						
KQSN300-M27-233	716	11	74	1480	233	30	DN300	DN300	298 kg
	342	17	61						
KQSN300-M27-223	570	14	79	1480	223	30	DN300	DN300	298 kg
	684	10	71						
KQSN300-M27-213	474	18	72	1480	213	30	DN300	DN300	298 kg
	790	13	86,5						
KQSN300-N27-251	948	10	81	1480	251	37	DN300	DN300	350 kg
	441	15	70						
KQSN300-N27-238	735	11	85	1480	238	30	DN300	DN300	298 kg
	882	8	79						
KQSN300-N27-213	422	14	68	1480	213	22	DN300	DN300	298 kg
	703	10	83						
	844	7	77	1480	765	1250	DN250	DN350	5560 kg
	403	13	66						
KQSN350-M4-765	672	9	81	1480	718	1000	DN250	DN350	5250 kg
	806	7	75						
KQSN350-M4-718	402	17	63	1480	693	900	DN250	DN350	5250 kg
	670	12	84						
KQSN350-M4-693	804	10	79	1480	666	800	DN250	DN350	4500 kg
	382	15	61						
KQSN350-M4-666	637	11	82	1480	765	1000	DN250	DN350	4500 kg
	764	9	77						
KQSN350-N4-765	342	12	59	1480	718	800	DN250	DN350	4500 kg
	570	9	80						
KQSN350-N4-718	684	7	75	1480	693	630	DN250	DN350	3900 kg
	756	220	68						
KQSN350-N4-693	1260	210	83	1480	666	500	DN250	DN350	3900 kg
	1660	192	77						
KQSN350-N4-666	733	195	67	1480	654	710	DN200	DN350	4550 kg
	1222	185	82						
KQSN350-M6-654	1610	163	76	1480	634	630	DN200	DN350	3460 kg
	703	128	64						

Tên nhóm: 5

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN350-M6-608	1172	110	80	1480	608	560	DN200	DN350	3460 kg
	1544	90	74						
KQSN350-M6-583	673	117	63	1480	583	500	DN200	DN350	3200 kg
	1121	103	79						
KQSN350-M6-543	1477	83	73	1480	543	400	DN200	DN350	3100 kg
	627	102	61						
KQSN350-M6-531	1046	88	77	1480	531	400	DN200	DN350	2900 kg
	1378	72	71						
KQSN350-N6-653	612	97	60	1480	653	500	DN200	DN350	3200 kg
	1021	85	76						
KQSN350-N6-627	1345	68	70	1480	627	500	DN200	DN350	3200 kg
	641	143	59						
KQSN350-N6-601	1069	121	82	1480	601	450	DN200	DN350	3100 kg
	1380	95	75						
KQSN350-N6-575	616	132	57	1480	575	400	DN200	DN350	2900 kg
	1026	112	80						
KQSN350-N6-530	1325	88	73	1480	530	315	DN200	DN350	2084 kg
	590	121	56						
KQSN350-M9-503	984	102	79	1480	503	355	DN300	DN350	1870 kg
	1270	80	72						
KQSN350-M9-473	565	111	54	1480	473	315	DN250	DN350	2084 kg
	941	94	77						
KQSN350-M9-453	1214	74	70	1480	453	280	DN250	DN350	1947 kg
	520	94	52						
KQSN350-M9-433	866	79	75	1480	433	250	DN250	DN350	1764 kg
	1141	65	68						
KQSN350-M9-415	756	86	70	1480	415	220	DN250	DN350	1705 kg
	1260	77	85						
KQSN350-N9-502	1512	68	81	1480	502	315	DN250	DN350	2084 kg
	711	77	69						
KQSN350-N9-477	1184	69	84	1480	477	250	DN250	DN350	1764 kg
	1421	61	80						
KQSN350-N9-452	680	71	68	1480	452	220	DN250	DN350	1705 kg
	1134	63	83						
KQSN350-M12S-395	1361	55	79	1480	395	185	DN300	DN350	1192 kg
	650	62	67						
KQSN350-M12S-375	1084	58	82	1480	375	160	DN300	DN350	1192 kg
	1300	52	78						
KQSN350-M12S-360	624	57	66	1480	360	132	DN300	DN350	1192 kg
	1040	53	81						
KQSN350-M12S-345	1247	46	77	1480	345	110	DN300	DN350	1018 kg
	641	83	63						
KQSN350-M12SJ-395	1069	74	85	990	395	55	DN300	DN350	530 kg
	1283	67	80						
KQSN350-M12S-330	609	75	61	990	330	110	DN300	DN350	1018 kg
	1016	66	83						
KQSN350-M12S-300	1219	59	78	990	300	110	DN300	DN350	1018 kg
	577	67	60						
KQSN350-M12S-270	962	59	82	990	270	110	DN300	DN350	1018 kg
	1155	53	77						
KQSN350-M12S-240	558	63	59	990	240	110	DN300	DN350	1018 kg
	940	56	81						
KQSN350-M12S-210	1116	50	76	990	210	110	DN300	DN350	1018 kg
	529	56	58						
KQSN350-M12S-180	882	50	80	990	180	110	DN300	DN350	1018 kg
	1058	46	75						
KQSN350-M12S-150	630	52	83	990	150	110	DN300	DN350	1018 kg
	1050	45	92						
KQSN350-M12S-120	1260	40	86	990	120	110	DN300	DN350	1018 kg
	598	46	82						
KQSN350-M12S-90	997	40	91	990	90	110	DN300	DN350	1018 kg
	1196	35	85						
KQSN350-M12S-60	574	43	81	990	60	110	DN300	DN350	1018 kg
	957	37	90						
KQSN350-M12S-30	1148	32	85	990	30	110	DN300	DN350	1018 kg
	550	40	80						
KQSN350-M12S-0	917	34	89	990	0	110	DN300	DN350	1018 kg
	1100	29	84						
KQSN350-M12S-0	526	36	79	990	0	110	DN300	DN350	1018 kg
	877	31	87						
KQSN350-M12S-0	1052	26	84	990	0	110	DN300	DN350	1018 kg
	420	23	83						
KQSN350-M12S-0	700	19	92	990	0	110	DN300	DN350	1018 kg
	0	0	0						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN350-M12SJ-375	840	17	89	990	375	45	DN300	DN350	495 kg
	399	21	82						
	665	17	91						
	798	15	88						
KQSN350-M12SJ-355	377	18	82	990	355	37	DN300	DN350	470 kg
	629	15	90						
	755	13	88						
KQSN350-M12SJ-330	351	16	81	990	330	30	DN300	DN350	350 kg
	585	13	90						
	702	11	88						
KQSN350-M12SJ-300	319	13	80	990	300	22	DN300	DN350	280 kg
	532	11	88						
	638	9	87						
KQSN350-M13-406	756	54	75	1480	406	220	DN300	DN350	1705 kg
	1260	46	87						
	1512	38	80						
KQSN350-M13-390	726	50	74	1480	390	185	DN300	DN350	1582 kg
	1210	42	86						
	1452	34	79						
KQSN350-M13-357	665	42	72	1480	357	160	DN300	DN350	1582 kg
	1109	35	85						
	1331	28	77						
KQSN350-M13-333	620	36	70	1480	333	132	DN300	DN350	1192 kg
	1033	31	84						
	1240	25	75						
KQSN350-M13J-406	506	24	75	990	406	75	DN300	DN350	954 kg
	843	21	87						
	1011	17	80						
KQSN350-M13J-390	485	22	74	990	390	55	DN300	DN350	530 kg
	809	19	86						
	971	16	79						
KQSN350-M13J-357	445	18	72	990	357	45	DN300	DN350	495 kg
	742	16	85						
	890	14	77						
KQSN350-M13J-333	415	16	70	990	333	37	DN300	DN350	470 kg
	691	14	84						
	829	12	75						
KQSN350-M14-362	585	39	77	1480	362	132	DN250	DN350	1192 kg
	975	33	89						
	1170	27	82						
KQSN350-M14-345	558	35	76	1480	345	110	DN250	DN350	1018 kg
	930	30	88						
	1116	25	81						
KQSN350-M14-327	529	32	75	1480	327	110	DN250	DN350	1018 kg
	882	27	87						
	1058	22	80						
KQSN350-M14-309	499	28	74	1480	309	90	DN250	DN350	615 kg
	831	24	86						
	998	20	79						
KQSN350-M14-289	467	25	73	1480	289	75	DN250	DN350	550 kg
	778	21	85						
	933	17	78						
KQSN350-N14-362	495	35	76	1480	362	110	DN250	DN350	1018 kg
	825	30	88						
	990	25	81						
KQSN350-N14-345	470	32	74	1480	345	90	DN250	DN350	615 kg
	783	27	86						
	939	22	79						
KQSN350-N14-327	443	28	73	1480	327	75	DN250	DN350	550 kg
	738	24	85						
	885	20	78						
KQSN350-N14-309	414	25	72	1480	309	75	DN250	DN350	550 kg
	690	21	84						
	828	17	77						
KQSN350-N14-288	383	21	71	1480	288	55	DN250	DN350	494 kg
	639	18	83						
	767	15	76						
KQSN350-M17S-345	756	37	86	1480	345	160	DN300	DN350	1192 kg
	1260	31	91,5						
	1512	25	86,5						
KQSN350-M17S-325	714	35	85	1480	325	132	DN300	DN350	1192 kg
	1190	29	90						
	1428	23	86						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN350-M17S-310	682	31	84,5	1480	310	110	DN300	DN350	1018 kg	
	1136	27	89							
	1363	21	86,2							
KQSN350-M17S-295	652	28	83	1480	295	90	DN300	DN350	615 kg	
	1087	24	88							
	1304	19	85,5							
KQSN350-M17S-285	622	26	81	1480	285	75	DN300	DN350	550 kg	
	1037	20	87,5							
	1245	17	87							
KQSN350-M17SJ-345	510	16	87	990	345	45	DN300	DN350	495 kg	
	850	14	91,5							
	1020	11	87							
KQSN350-M17SJ-325	480	14	86,1	990	325	37	DN300	DN350	470 kg	
	800	12	91							
	960	9	86,3							
KQSN350-M17SJ-310	456	12	86	990	310	30	DN300	DN350	350 kg	
	760	10	90,5							
	912	8	86,2							
KQSN350-M17SJ-295	438	10	85,5	990	295	30	DN300	DN350	350 kg	
	730	8	89							
	876	7	85,8							
KQSN350-M17SJ-285	420	9	84	990	285	22	DN300	DN350	280 kg	
	700	7	87,5							
	840	6	85							
KQSN350-M20S-320	660	28	85	1480	320	90	DN300	DN350	615 kg	
	1100	23	90							
	1320	18	86							
KQSN350-M20S-304	628	26	85	1480	304	90	DN300	DN350	615 kg	
	1046	21	89							
	1255	16	86							
KQSN350-M20S-289	596	24	84	1480	289	75	DN300	DN350	550 kg	
	993	19	89							
	1192	15	85							
KQSN350-M20S-273	563	22	83	1480	273	75	DN300	DN350	550 kg	
	939	17	87							
	1127	13	84							
KQSN350-M20S-257	531	19	83	1480	257	55	DN300	DN350	494 kg	
	885	15	86							
	1065	11	84							
KQSN350-M20SJ-320	442	13	85	990	320	30	DN300	DN350	350 kg	
	736	10	90							
	883	8	84							
KQSN350-M20SJ-304	419	12	84	990	304	22	DN300	DN350	280 kg	
	699	9	89							
	839	7	84							
KQSN350-M20SJ-289	399	11	82	990	289	22	DN300	DN350	280 kg	
	665	8	88							
	798	6	85							
KQSN350-M20SJ-273	377	10	81	990	273	18.5	DN300	DN350	275 kg	
	628	7	87							
	754	5	84							
KQSN350-M27-290	756	23	78	1480	290	75	DN350	DN350	550 kg	
	1260	17	88							
	1512	14	77							
KQSN350-M27-273	711	20	76	1480	273	75	DN350	DN350	550 kg	
	1184	15	86							
	1421	11	75							
KQSN350-M27-255	665	18	73	1480	255	55	DN350	DN350	494 kg	
	1109	13	83							
	1311	10	72							
KQSN350-M27-247	643	17	72	1480	247	55	DN350	DN350	494 kg	
	1071	12	82							
	1285	9	71							
KQSN350-N27-290	641	22	70	1480	290	75	DN350	DN350	550 kg	
	1069	16	87							
	1283	14	76							
KQSN350-N27-267	590	19	68	1480	267	55	DN350	DN350	494 kg	
	984	14	85							
	1180	12	74							
KQSN350-N27-247	545	16	65	1480	247	45	DN350	DN350	494 kg	
	909	12	82							
	1091	10	71							
Tên nhóm: 6										

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN400-M4-900	1410	306	75,6	1480	900	2500	DN300	DN400	10600 kg
	2350	278	84						
	2938	226	76,4						
KQSN400-M4-835	1354	281	74,7	1480	835	2240	DN300	DN400	10600 kg
	2256	256	83						
	2820	208	76,4						
KQSN400-M4-775	1286	256	73,8	1480	775	2000	DN300	DN400	10600 kg
	2143	233	82						
	2679	189	75,4						
KQSN400-M4-705	1212	233	72,9	1480	705	1800	DN300	DN400	7150 kg
	2036	212	81						
	2545	172	74,5						
KQSN400-M4-630	1148	207	72	1480	630	1600	DN300	DN400	7150 kg
	1914	189	80						
	2392	153	74						
KQSN400-N4-900	1212	286	74,7	1480	900	2240	DN300	DN400	10600 kg
	2020	260	83						
	2525	211	76,4						
KQSN400-N4-835	1164	264	73,8	1480	835	2000	DN300	DN400	10600 kg
	1940	240	82						
	2425	195	75,4						
KQSN400-N4-775	1106	241	72,9	1480	775	1800	DN300	DN400	7150 kg
	1843	219	81						
	2304	178	74,5						
KQSN400-N4-705	1050	220	72	1480	705	1600	DN300	DN400	7150 kg
	1750	200	80						
	2188	163	73,6						
KQSN400-N4-630	988	196	71	1480	630	1400	DN300	DN400	7150 kg
	1646	178	79						
	2058	145	73						
KQSN400-M6W-725	1211	180	78	1480	725	1250	DN300	DN400	9900 kg
	2018	160	86						
	2523	151	84						
KQSN400-M6W-675	1151	157	78	1480	675	1000	DN300	DN400	8300 kg
	1918	137	85						
	2398	120	83						
KQSN400-M6W-620	1091	130	78	1480	620	800	DN300	DN400	6060 kg
	1818	111	84						
	2273	97	82						
KQSN400-M6W-570	1025	108	77	1480	570	630	DN300	DN400	6060 kg
	1708	91	83						
	2135	76	78						
KQSN400-N6W-724	1079	176	78	1480	724	1120	DN300	DN400	8300 kg
	1798	150	85						
	2248	134	81						
KQSN400-N6W-674	983	146	76	1480	674	800	DN300	DN400	6060 kg
	1638	125	83						
	2048	108	81						
KQSN400-N6W-619	929	123	76	1480	619	630	DN300	DN400	6060 kg
	1548	105	82						
	1935	89	81						
KQSN400-N6W-570	875	98	74	1480	570	450	DN300	DN400	4490 kg
	1458	81	81						
	1823	68	80						
KQSN400-M9W-573	1211	107	79	1480	573	710	DN300	DN400	6030 kg
	2018	94	87						
	2523	81	83						
KQSN400-M9W-526	1123	89	78	1480	526	560	DN300	DN400	6030 kg
	1872	77	85						
	2340	66	83						
KQSN400-M9W-486	1075	74	77	1480	486	450	DN300	DN400	4490 kg
	1792	63	84						
	2240	53	82						
KQSN400-M9W-446	1045	62	74	1480	446	355	DN300	DN400	4490 kg
	1742	51	83						
	2125	41	77						
KQSN400-N9W-585	1110	112	78	1480	585	630	DN300	DN400	6030 kg
	1850	92	86						
	2313	74	82						
KQSN400-N9W-573	1039	96	78	1480	573	500	DN300	DN400	6030 kg
	1732	80	85						
	2165	67	82						
	943	82	76						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN400-N9W-526	1572	68	84	1480	526	400	DN300	DN400	4490 kg
	1965	58	82						
KQSN400-N9W-486	901	70	73	1480	486	355	DN300	DN400	4490 kg
	1502	59	83						
KQSN400-N9W-446	1878	49	81	1480	446	280	DN300	DN400	1947 kg
	877	58	73						
KQSN400-M13W-481	1462	48	82	1480	481	450	DN300	DN400	4490 kg
	1828	40	80						
KQSN400-M13W-470	1215	71	75	1480	470	400	DN300	DN400	4490 kg
	2025	59	89						
KQSN400-M13W-438	2520	51	85	1480	438	315	DN300	DN400	3060 kg
	1211	65	76						
KQSN400-M13W-406	2018	52	88	1480	406	250	DN300	DN400	2180 kg
	2502	43	85						
KQSN400-M13W-374	1148	57	75	1480	374	185	DN300	DN400	1890 kg
	1914	45	87						
KQSN400-N13W-481	2393	37	84	1480	481	400	DN300	DN400	4490 kg
	1082	47	76						
KQSN400-N13W-470	1804	37	86	1480	470	315	DN300	DN400	2180 kg
	2255	27	79						
KQSN400-N13W-438	1016	38	73	1480	438	280	DN300	DN400	1890 kg
	1694	28	85						
KQSN400-N13W-406	2118	20	78	1480	406	220	DN300	DN400	1128 kg
	859	39	73						
KQSN400-N13W-374	1432	31	84	1480	374	185	DN300	DN400	1128 kg
	1790	23	79						
KQSN400-M17S-385	1089	47	84	1480	385	250	DN350	DN400	1764 kg
	1815	40	90						
KQSN400-M17S-365	2178	31	85	1480	365	220	DN350	DN400	1705 kg
	1020	44	83						
KQSN400-M17S-350	1700	38	89	1480	350	200	DN350	DN400	1282 kg
	2040	28	84						
KQSN400-M17S-335	972	39	82	1480	335	185	DN350	DN400	1192 kg
	1620	34	88						
KQSN400-M17S-320	1944	24	83	1480	320	160	DN350	DN400	1192 kg
	930	36	81						
KQSN400-M17SJ-385	1550	31	87	990	385	90	DN350	DN400	1120 kg
	1860	26	82						
KQSN400-M17SJ-365	888	28	80	990	365	75	DN350	DN400	954 kg
	1480	25	85						
KQSN400-M17SJ-350	1776	20	81	990	350	75	DN350	DN400	954 kg
	728	21	84						
KQSN400-M17SJ-335	1214	18	90	990	335	55	DN350	DN400	530 kg
	1457	14	87						
KQSN400-M19W-402	682	20	83	1480	402	220	DN350	DN400	1705 kg
	1137	17	89						
KQSN400-M19W-377	1365	13	87	1480	377	200	DN350	DN400	1582 kg
	650	17	82						
	1084	15	88						
	1300	11	87						
	622	16	81						
	1037	14	87						
	1244	12	85						
	594	13	80						
	990	11	86,5						
	1188	9	86						
	1211	43	75						
	2018	32	89						
	2523	24	81						
	1181	37	75						
	1968	27	88						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN400-M19W-352		2460	19	80	1480	352	160	DN350	DN400	1192 kg
		1151	31	74						
		1918	22	87						
		2398	13	79						
KQSN400-M19W-337		1121	25	73	1480	337	110	DN350	DN400	1192 kg
		1868	16	86						
		2335	8	75						
KQSN400-N19W-402		1039	39	76	1480	402	200	DN350	DN400	1582 kg
		1732	31	88						
		2165	24	85						
KQSN400-N19W-377		985	34	76	1480	377	160	DN350	DN400	1192 kg
		1642	27	87						
		2053	20	82						
KQSN400-N19W-352		943	29	74	1480	352	132	DN350	DN400	1192 kg
		1572	23	85						
		1965	16	81						
KQSN400-N19W-337		901	25	73	1480	337	110	DN350	DN400	1018 kg
		1502	18	84						
		1878	12	79						
Tên nhóm: 7										
KQSN450-M5-810		1428	247	75	1480	810	2000	DN350	DN450	9080 kg
		2380	220	80						
		2856	189	76						
KQSN450-M5-770		1357	223	74	1480	770	1800	DN350	DN450	9080 kg
		2262	199	79						
		2715	171	75						
KQSN450-M5-730		1287	201	73	1480	730	1600	DN350	DN450	7827 kg
		2145	179	78						
		2574	154	74						
KQSN450-M5-690		1216	179	72	1480	690	1250	DN350	DN450	7827 kg
		2027	160	77						
		2433	137	73						
KQSN450-M5-650		1146	159	71	1480	650	1120	DN350	DN450	6080 kg
		1910	142	76						
		2292	122	72						
KQSN450-M5J-810		952	110	75	990	810	630	DN350	DN450	5230 kg
		1587	98	80						
		1983	84	76						
KQSN450-M5J-770		905	99	74	990	770	560	DN350	DN450	4080 kg
		1508	88	79						
		1885	76	75						
KQSN450-M5J-730		858	89	73	990	730	450	DN350	DN450	4080 kg
		1430	79	78						
		1787	68	74						
KQSN450-M5J-690		811	80	72	990	690	400	DN350	DN450	3155 kg
		1352	71	77						
		1690	61	73						
KQSN450-M5J-650		764	71	71	990	650	355	DN350	DN450	3155 kg
		1273	63	76						
		1592	54	72						
KQSN450-M6-850		1890	254	78,3	1480	850	2800	DN350	DN450	12500 kg
		3150	231	87						
		3938	193	79,1						
KQSN450-M6-788		1814	231	77,4	1480	788	2500	DN350	DN450	10600 kg
		3024	210	86						
		3780	175	79,1						
KQSN450-M6-730		1724	210	76,5	1480	730	2240	DN350	DN450	10600 kg
		2873	191	85						
		3591	159	78,2						
KQSN450-M6-664		1638	192	75,6	1480	664	2000	DN350	DN450	10600 kg
		2729	174	84						
		3412	145	77,3						
KQSN450-M6-595		1539	170	75	1480	595	1800	DN350	DN450	10600 kg
		2565	155	83						
		3207	129	76						
KQSN450-N6-850		1632	240	74,7	1480	850	2500	DN350	DN450	10600 kg
		2720	218	83						
		3400	182	76,4						
KQSN450-N6-788		1567	435	73,8	1480	788	2240	DN350	DN450	10600 kg
		2611	201	82						
		3264	907	75,4						
KQSN450-N6-730		1488	201	72,9	1480	730	2000	DN350	DN450	10600 kg
		2481	183	81						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN450-N6-664		3100	152	74,5	1480	664	1800	DN350	DN450	10600 kg
		1414	183	72						
		2357	166	80						
		2946	138	73,6						
KQSN450-N6-595		1329	163	71	1480	595	1600	DN350	DN450	7150 kg
		2215	148	79						
		2769	123	73						
KQSN450-M8W-673		1907	1664	79	1480	673	1600	DN350	DN450	10400 kg
		3178	144	87						
		3813	127	83						
KQSN450-M8W-615		1796	135	78	1480	615	1250	DN350	DN450	10400 kg
		2994	116	86						
		3593	101	82						
KQSN450-M8W-568		1718	113	76	1480	568	1000	DN350	DN450	8050 kg
		2863	95	85						
		3435	83	81						
KQSN450-M8W-518		1655	95	75	1480	518	800	DN350	DN450	6060 kg
		2759	77	84						
		3311	66	79						
KQSN450-N8W-673		1693	147	78	1480	673	1250	DN350	DN450	10400 kg
		2821	123	85						
		3385	107	81						
KQSN450-N8W-615		1583	123	77	1480	615	1000	DN350	DN450	8050 kg
		2639	103	84						
		3467	87	80						
KQSN450-N8W-568		1487	107	74	1480	568	800	DN350	DN450	6060 kg
		2479	87	83						
		2975	75	79						
KQSN450-N8W-518		1401	89	74	1480	518	630	DN350	DN450	6060 kg
		2335	73	82						
		2802	63	79						
KQSN450-M12W-538		1908	89	77	1480	538	900	DN350	DN450	7800 kg
		3180	76	89						
		3975	64	80						
KQSN450-M12W-502		1776	80	77	1480	502	710	DN350	DN450	6060 kg
		2960	66	87						
		3700	54	79						
KQSN450-M12W-465		1716	69	76	1480	465	560	DN350	DN450	6060 kg
		2860	55	85						
		3575	41	77						
KQSN450-M12W-428		1614	56	75	1480	428	450	DN350	DN450	4490 kg
		2690	44	82						
		3363	33	76						
KQSN450-N12W-538		1614	89	78	1480	538	710	DN350	DN450	6060 kg
		2690	73	88						
		3363	62	84						
KQSN450-N12W-502		1494	80	76	1480	502	560	DN350	DN450	6060 kg
		2490	66	87						
		3113	51	83						
KQSN450-N12W-465		1392	69	75	1480	465	450	DN350	DN450	4490 kg
		2320	56	85						
		2900	46	82						
KQSN450-N12W-428		1368	57	75	1480	428	400	DN350	DN450	4490 kg
		2280	46	83						
		2850	35	75						
Tên nhóm: 8										
KQSN500-M6-860		1298	108	75	990	860	800	DN300	DN500	5050 kg
		2163	100	85						
		2596	90	80						
KQSN500-M6-834		1206	101	73	990	834	710	DN300	DN500	5050 kg
		2010	93	83						
		2412	85	79						
KQSN500-M6-791		1194	92	71	990	791	630	DN300	DN500	5050 kg
		1990	94	81						
		2388	75	79						
KQSN500-M6-757		1142	85	69	990	757	560	DN300	DN500	5050 kg
		1904	77	79						
		2285	69	77						
KQSN500-M6-705		1064	75	67	990	705	500	DN300	DN500	5050 kg
		1773	67	77						
		2128	60	76						
KQSN500-N6-860		1028	103	71	990	860	630	DN300	DN500	5050 kg
		1717	95	88						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN500-N6-817	2057	88	81	990	817	560	DN300	DN500	5050 kg
	977	94	69						
	1628	86	86						
	1954	80	80						
KQSN500-N6-783	936	87	67	990	783	500	DN300	DN500	5050 kg
	1560	79	84						
	1872	72	79						
KQSN500-N6-748	895	80	65	990	748	450	DN300	DN500	3377 kg
	1491	72	82						
	1789	65	78						
KQSN500-N6-705	843	72	63	990	705	400	DN300	DN500	3377 kg
	1406	64	80						
	1687	57	77						
KQSN500-M6W-940	1902	151	76	990	940	1400	DN400	DN500	11500 kg
	2900	135	88						
	3600	115	82						
KQSN500-M6W-880	1826	130	74	990	880	1250	DN400	DN500	11500 kg
	2715	118	87						
	3200	105	80						
KQSN500-M6W-825	1731	115	72	990	825	1000	DN400	DN500	11500 kg
	2545	104	86						
	3000	87	78						
KQSN500-M6W-770	1598	99	70	990	770	800	DN400	DN500	8300 kg
	2375	91	84						
	2800	75	76						
KQSN500-N6W-940	1611	147	75	990	940	1250	DN400	DN500	11500 kg
	2500	130	87						
	3100	117	83						
KQSN500-N6W-880	1521	129	74	990	880	1000	DN400	DN500	11500 kg
	2340	115	86						
	2880	103	82						
KQSN500-N6W-825	1427	114	72	990	825	900	DN400	DN500	8300 kg
	2195	101	85						
	2650	90	79						
KQSN500-N6W-770	1335	54	70	990	770	710	DN400	DN500	8300 kg
	2050	87	83						
	2450	77	76						
KQSN500-M9-675	1212	68	83	990	675	450	DN350	DN500	3377 kg
	2020	60	91						
	2424	55	88						
KQSN500-M9-648	1164	63	81	990	648	400	DN350	DN500	3295 kg
	1939	55	89						
	2327	49	86						
KQSN500-M9-621	1115	58	79	990	621	355	DN350	DN500	3295 kg
	1858	50	87						
	2230	44	84						
KQSN500-M9-587	1054	53	77	990	587	315	DN350	DN500	3295 kg
	1757	45	85						
	2109	39	82						
KQSN500-M9-554	994	49	75	990	554	280	DN350	DN500	3295 kg
	1656	40	83						
	1988	34	80						
KQSN500-N9-675	1092	66	75	990	675	355	DN350	DN500	3295 kg
	1820	56	91						
	2184	51	87						
KQSN500-N9-647	1048	60	73	990	647	315	DN350	DN500	3295 kg
	1747	52	89						
	2094	46	85						
KQSN500-N9-613	994	55	71	990	613	280	DN350	DN500	3295 kg
	1656	47	87						
	1987	41	83						
KQSN500-N9-587	950	52	69	990	587	250	DN350	DN500	3295 kg
	1583	42	85						
	1900	38	81						
KQSN500-N9-574	874	47	67	990	574	250	DN350	DN500	3295 kg
	1457	36	83						
	1748	33	79						
KQSN500-M11W-540	2120	93	87	1480	540	900	DN400	DN500	7800 kg
	2650	86	89						
	3180	76	85						
KQSN500-M11W-520	2016	86	86	1480	520	800	DN400	DN500	6060 kg
	2520	79	88						
	3024	68	86						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN500-M11W-500	1904	79	86	1480	500	630	DN400	DN500	6061 kg
	2380	71	87						
	2856	62	86						
KQSN500-M11W-480	1816	72	85	1480	480	560	DN400	DN500	6062 kg
	2270	65	86						
	2724	56	84						
KQSN500-M11W-460	1772	64	84	1480	460	500	DN400	DN500	6063 kg
	2215	58	85						
	2658	50	82						
KQSN500-N11W-495	1760	72	86	1480	495	560	DN400	DN500	6060 kg
	2200	63	88						
	2640	53	85						
KQSN500-N11W-475	1616	65	85	1480	475	450	DN400	DN500	4490 kg
	2020	58	87						
	2424	49	85						
KQSN500-N11W-450	1496	58	84	1480	450	400	DN400	DN500	4491 kg
	1870	51	86						
	2244	44	83						
KQSN500-N11W-425	1416	50	82	1480	425	355	DN400	DN500	4492 kg
	1770	47	85						
	2124	37	81						
KQSN500-M12S-515	1470	80	86,4	1480	515	630	DN400	DN500	4170 kg
	2450	74	92						
	2940	69	89,6						
KQSN500-M12S-485	1384	78	86,2	1480	485	560	DN400	DN500	4170 kg
	2307	68	91,5						
	2768	63	89						
KQSN500-M12S-470	1341	69	86	1480	470	500	DN400	DN500	3970 kg
	2235	62	90,6						
	2682	57	89						
KQSN500-M12S-450	1284	64	86	1480	450	450	DN400	DN500	3970 kg
	2140	55	90,2						
	2568	51	88,3						
KQSN500-M12S-430	1227	55	86	1480	430	400	DN400	DN500	3970 kg
	2045	49	89						
	2454	45	87,5						
KQSN500-M12SJ-515	936	39	83	990	515	185	DN400	DN500	1685 kg
	1560	34	92						
	1872	30	88						
KQSN500-M12SJ-485	882	36	82,5	990	485	160	DN400	DN500	1645 kg
	1470	31	91,8						
	1764	26	88						
KQSN500-M12SJ-470	854	33	82	990	470	160	DN400	DN500	1645 kg
	1423	28	90,5						
	1708	25	87,5						
KQSN500-M12SJ-450	818	31	82	990	450	132	DN400	DN500	1239 kg
	1363	26	90,1						
	1636	23	87,2						
KQSN500-M12SJ-430	781	27	81,5	990	430	132	DN400	DN500	1239 kg
	1302	24	89,5						
	1562	22	87						
KQSN500-M13-530	1320	46	79	990	530	280	DN350	DN500	2100 kg
	2200	36	89						
	2640	29	85						
KQSN500-M13-519	1292	44	78	990	519	280	DN350	DN500	2100 kg
	2154	35	88						
	2585	27	84						
KQSN500-M13-498	1240	40	77	990	498	250	DN350	DN500	2053 kg
	2067	32	87						
	2480	24	83						
KQSN500-M13-477	1188	37	76	975	477	220	DN350	DN500	1922 kg
	1980	30	86						
	2376	23	82						
KQSN500-M13-461	1148	34	75	975	461	200	DN350	DN500	1779 kg
	1914	28	85						
	2297	21	81						
KQSN500-M13-440	1096	31	74	990	440	185	DN350	DN500	1685 kg
	1826	25	84						
	2191	19	80						
KQSN500-N13-530	1028	45	71	990	530	220	DN350	DN500	1922 kg
	1714	35	89						
	2057	28	84						
	977	40	69						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN500-N13-504	1628	31	87	990	504	185	DN350	DN500	1685 kg
	1954	26	82						
KQSN500-N13-477	926	36	67	990	477	160	DN350	DN500	1645 kg
	1543	28	85						
KQSN500-N13-440	1851	23	80	990	440	132	DN350	DN500	1239 kg
	854	31	65						
KQSN500-M17S-432	1423	24	83	1480	432	450	DN400	DN500	3520 kg
	1707	20	78						
KQSN500-M17S-410	1500	58	86	1480	410	400	DN400	DN500	3520 kg
	2500	49	90,5						
KQSN500-M17S-391	3000	42	88	1480	391	355	DN400	DN500	2084 kg
	1440	52	86						
KQSN500-M17S-374	2400	44	89,5	1480	374	280	DN400	DN500	1947 kg
	2880	38	87						
KQSN500-M17S-354	1358	45	85	1480	354	250	DN400	DN500	1764 kg
	2264	40	88,5						
KQSN500-M17SJ-432	2717	35	86	990	432	132	DN400	DN500	1239 kg
	1299	42	85						
KQSN500-M17SJ-410	2165	37	87,5	990	410	110	DN400	DN500	1211 kg
	2598	30	85						
KQSN500-M17SJ-391	1240	38	84	990	391	110	DN400	DN500	1211 kg
	2067	34	87						
KQSN500-M17SJ-374	2480	29	86	990	374	90	DN400	DN500	1120 kg
	1005	26	87						
KQSN500-M17SJ-354	1675	22	90,5	990	354	75	DN400	DN500	954 kg
	2010	21	88						
KQSN500-M19-452	965	23	87	990	452	160	DN400	DN500	1645 kg
	1608	20	89,5						
KQSN500-M19-434	1930	18	87	990	434	160	DN400	DN500	1239 kg
	910	21	86						
KQSN500-M19-407	1517	18	88,5	990	407	132	DN400	DN500	1239 kg
	1820	16	87						
KQSN500-M19-371	871	19	86	990	371	110	DN400	DN500	1211 kg
	1451	16	88						
KQSN500-N19-452	1741	14	86	990	452	160	DN400	DN500	1645 kg
	831	21	85						
KQSN500-N19-420	1385	14	87	990	420	132	DN400	DN500	1239 kg
	1662	15	86						
KQSN500-N19-389	1212	26	74	990	389	90	DN400	DN500	1120 kg
	2020	23	89						
KQSN500-N19-371	2424	19	88	990	371	90	DN400	DN500	1120 kg
	1164	24	72						
KQSN500-M20S-410	1939	20	87	1480	410	315	DN400	DN500	2084 kg
	2327	17	86						
KQSN500-M20S-390	1091	21	70	1480	390	280	DN400	DN500	1947 kg
	1818	18	85						
KQSN500-M20S-370	2182	15	84	1480	370	250	DN400	DN500	1764 kg
	994	17	68						
KQSN500-M20S-350	1656	15	83	1480	350	200	DN400	DN500	1582 kg
	1988	13	82						
	1028	25	67						
	1714	22	89						
	2057	18	87						
	956	22	65						
	1594	19	87						
	1913	16	85						
	884	18	63						
	1474	16	85						
	1769	13	83						
	843	17	61						
	1406	15	83						
	1687	12	81						
	1425	46	84						
	2375	38	91						
	2850	31	87						
	1355	43	83						
	2259	35	90						
	2711	28	87						
	1286	40	82						
	2143	31	89						
	2572	25	86						
	1216	34	81						
	2027	28	88						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN500-M20S-330		2432	22	85	1480	330	185	DN400	DN500	1582 kg
		1147	31	80						
		1912	25	87						
		2294	19	84						
KQSN500-M20SJ-410		952	21	84	990	410	110	DN400	DN500	1211 kg
		1587	17	91						
		1904	15	87						
KQSN500-M20SJ-390		906	18	83	990	390	90	DN400	DN500	1120 kg
		1510	15	90						
		1812	13	86						
KQSN500-M20SJ-370		859	17	82	990	370	75	DN400	DN500	954 kg
		1432	14	89						
		1718	11	85						
KQSN500-M20SJ-350		813	15	81	990	350	75	DN400	DN500	954 kg
		1355	12	88						
		1626	10	84						
KQSN500-M20SJ-330		766	13	80	990	330	55	DN400	DN500	530 kg
		1277	11	87						
		1532	9	83						
KQSN500-M28-390		1290	17	80	990	390	110	DN500	DN500	1211 kg
		2150	14	86						
		2580	10	84						
KQSN500-M28-371		1151	15	78	990	371	90	DN500	DN500	1120 kg
		1919	12	84						
		2303	8	82						
KQSN500-M28-347		1079	13	76	990	347	75	DN500	DN500	954 kg
		1798	10	82						
		2157	8	80						
KQSN500-M28-332		1030	12	74	990	332	75	DN500	DN500	954 kg
		1717	9	80						
		2060	7	78						
KQSN500-N28-390		1080	16	72	990	390	90	DN500	DN500	1120 kg
		1800	14	85						
		2160	10	82						
KQSN500-N28-374		1037	15	70	990	374	75	DN500	DN500	954 kg
		1728	12	83						
		2074	9	81						
KQSN500-N28-351		972	13	68	990	351	75	DN500	DN500	954 kg
		1620	11	81						
		1944	8	79						
KQSN500-N28-332		874	11	66	990	332	75	DN500	DN500	954 kg
		1457	9	79						
		1748	6	77						
Tên nhóm: 9										
KQSN600-M6-1040		2400	174	76,5	990	1040	2500	DN450	DN600	12500 kg
		4000	158	85						
		5000	129	77,3						
KQSN600-M6-964		2304	158	75,6	990	964	2240	DN450	DN600	12500 kg
		3840	144	84						
		4800	117	77,3						
KQSN600-M6-893		2189	144	74,7	990	893	2000	DN450	DN600	12500 kg
		3648	131	83						
		4560	106	76,4						
KQSN600-M6-812		2079	131	73,8	990	812	1800	DN450	DN600	10500 kg
		3466	119	82						
		4332	97	75,4						
KQSN600-M6-730		1955	117	73	990	730	1600	DN450	DN600	10500 kg
		3258	106	81,5						
		4072	86	75						
KQSN600-N6-1040		2154	165	74,7	990	1040	2240	DN450	DN600	12500 kg
		3590	150	83						
		4488	122	76,4						
KQSN600-N6-964		2068	152	73,8	990	964	2000	DN450	DN600	12500 kg
		3446	138	82						
		4308	112	75,4						
KQSN600-N6-893		1964	138	72,9	990	893	1800	DN450	DN600	10500 kg
		3274	126	81						
		4093	102	74,5						
KQSN600-N6-812		1866	126	72	990	812	1600	DN450	DN600	10500 kg
		3110	114	80						
		3888	93	73,6						
KQSN600-N6-730		1754	112	71	990	730	1400	DN450	DN600	10500 kg
		2924	102	79						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN600-M8-940	3655	83	73	990	940	2000	DN500	DN600	10500 kg
	3040	124	79						
	5069	116	90						
	6080	93	82						
KQSN600-M8-920	2535	122	78	990	920	1800	DN500	DN600	10500 kg
	4230	112	89						
	5285	89	81						
KQSN600-M8-870	2400	111	76	990	870	1600	DN500	DN600	10500 kg
	4000	101	87						
	5000	81	79						
KQSN600-M8-825	2280	100	74	990	825	1250	DN500	DN600	6290 kg
	3800	91	85						
	4750	73	77						
KQSN600-M8-775	2100	89	72	990	775	1120	DN500	DN600	6290 kg
	3500	81	83						
	4375	65	75						
KQSN600-N8-840	2160	99	77	990	840	1250	DN500	DN600	6290 kg
	3600	90	88,5						
	4500	72	80						
KQSN600-N8-805	2100	91	75	990	805	1000	DN500	DN600	6290 kg
	3500	83	86						
	4375	65	78						
KQSN600-N8-770	2020	86	73	990	770	1000	DN500	DN600	6290 kg
	3370	78	84						
	4210	62	76						
KQSN600-N8-735	1935	78	71	990	735	900	DN500	DN600	6290 kg
	3230	71	82						
	4035	57	74						
KQSN600-N8-700	1840	73	70	990	700	800	DN500	DN600	5050 kg
	3070	66	80						
	3835	53	72						
KQSN600-M9-782	1902	85	76	990	782	900	DN400	DN600	6085 kg
	3170	76	89						
	3804	66	82						
KQSN600-M9-751	1826	78	74	990	751	800	DN400	DN600	5050 kg
	3043	70	87						
	3652	61	80						
KQSN600-M9-712	1731	70	72	990	712	710	DN400	DN600	5050 kg
	2885	63	85						
	3462	54	78						
KQSN600-M9-657	1598	60	70	990	657	560	DN400	DN600	5050 kg
	2663	53	83						
	3195	46	76						
KQSN600-N9-782	1614	82	68	990	782	710	DN400	DN600	5050 kg
	2690	73	87						
	3228	64	81						
KQSN600-N9-767	1582	71	66	990	766	630	DN400	DN600	5050 kg
	2636	63	85						
	3163	55	79						
KQSN600-N9-719	1485	65	64	990	719	560	DN400	DN600	5050 kg
	2475	58	83						
	2970	50	77						
KQSN600-N9-680	1404	60	62	990	680	500	DN400	DN600	5050 kg
	2340	54	81						
	2808	47	75						
KQSN600-N9-657	1356	54	60	990	657	450	DN400	DN600	3377 kg
	2360	48	79						
	2711	42	73						
KQSN600-M10-700	3038	166	80	1480	700	2800	DN500	DN600	11710 kg
	5064	150	89						
	6077	131	86						
KQSN600-M10-670	2898	151	80	1480	670	2500	DN500	DN600	11710 kg
	4830	136	88						
	5796	120	85						
KQSN600-M10-635	2754	136	79	1480	635	2240	DN500	DN600	14000 kg
	4590	123	87						
	5508	108	84						
KQSN600-M10-605	2616	123	78	1480	605	2000	DN500	DN600	14000 kg
	4360	111	86						
	5232	97	83						
KQSN600-M10-575	2484	110	77	1480	575	1800	DN500	DN600	14000 kg
	4140	100	84						
	4968	88	82						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN600-M10J-825	2460	94	79,5	990	825	1250	DN500	DN600	11500 kg
	4100	85	90,5						
	4920	78	86						
KQSN600-M10J-790	2376	89	81,5	990	790	1120	DN500	DN600	11500 kg
	3960	80	89						
	4752	75	85,5						
KQSN600-M10J-750	2256	79	81	990	750	1000	DN500	DN600	11500 kg
	3760	72	87,5						
	4512	63	81						
KQSN600-M10J-710	2136	70	77,5	990	710	900	DN500	DN600	8300 kg
	3560	65	85,5						
	4272	55	79						
KQSN600-M10J-670	2015	62	74	990	670	800	DN500	DN600	8300 kg
	3358	58	83						
	4030	49	76						
KQSN600-N10-710	3132	161	80,5	1480	710	2500	DN500	DN600	11710 kg
	5220	140	88,5						
	6264	120	83						
KQSN600-N10-675	2978	144	78	1480	675	2240	DN500	DN600	14000 kg
	4963	126	87						
	5955	109	80						
KQSN600-N10-640	2823	127	77	1480	640	2000	DN500	DN600	14000 kg
	4705	111	86						
	5646	98	80						
KQSN600-N10-605	2668	111	76	1480	605	1800	DN500	DN600	14000 kg
	4447	97	85						
	5337	86	78						
KQSN600-N10J-710	2095	72	79	990	710	800	DN500	DN600	8300 kg
	3492	63	88						
	4190	54	83,5						
KQSN600-N10J-675	1992	64	77,5	990	675	710	DN500	DN600	8300 kg
	3320	57	87						
	3984	49	83						
KQSN600-N10J-640	1888	57	76,5	990	640	560	DN500	DN600	7100 kg
	3147	50	85,5						
	3777	44	82						
KQSN600-N10J-605	1785	50	75,5	990	605	500	DN500	DN600	7100 kg
	2975	44	84,5						
	3570	39	81						
KQSN600-M12S-617	2424	120	82	1480	617	1600	DN500	DN600	8073 kg
	4040	105	91						
	4848	93	86						
KQSN600-M12S-580	2279	108	81	1480	580	1250	DN500	DN600	7564 kg
	3798	93	89,5						
	4558	84	87						
KQSN600-M12S-550	2461	97	81	1480	550	1120	DN500	DN600	6080 kg
	3601	84	88,5						
	4321	77	88						
KQSN600-M12S-520	2042	84	80	1480	520	1000	DN500	DN600	5880 kg
	3404	75	86						
	4085	67	84						
KQSN600-M12SJ-617	1620	53	82	990	617	400	DN500	DN600	3980 kg
	2700	46	91						
	3240	39	87,5						
KQSN600-M12SJ-580	1523	47	82	990	580	355	DN500	DN600	3870 kg
	2538	41	89,5						
	3046	35	87,5						
KQSN600-M12SJ-550	1444	42	81	990	550	315	DN500	DN600	3770 kg
	2407	37	88,5						
	2888	32	87						
KQSN600-M12SJ-520	1365	37	80	990	520	280	DN500	DN600	1710 kg
	2275	33	87						
	2730	28	86						
KQSN600-M13-631	1932	59	78	990	631	560	DN400	DN600	4600 kg
	3220	48	89						
	3864	38	81						
KQSN600-M13-618	1864	56	76	990	618	500	DN400	DN600	4600 kg
	3107	46	87						
	3728	36	79						
KQSN600-M13-593	1788	52	74	990	593	450	DN400	DN600	3377 kg
	2980	42	85						
	3576	33	77						
	1712	47	72						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN600-M13-568	2853	38	83	990	568	400	DN400	DN600	3400 kg
	3424	30	75						
KQSN600-M13-540	1626	43	70	990	540	355	DN400	DN600	3100 kg
	2710	35	81						
KQSN600-M13J-631	3252	27	73	740	631	220	DN400	DN600	3590 kg
	1444	33	78						
KQSN600-M13J-618	2407	27	89	740	618	220	DN400	DN600	3590 kg
	2888	21	81						
KQSN600-M13J-593	1414	32	76	740	593	220	DN400	DN600	3590 kg
	2357	26	87						
KQSN600-M13J-568	2829	20	79	740	568	185	DN400	DN600	1900 kg
	1357	29	74						
KQSN600-M13J-540	2262	24	85	740	540	160	DN400	DN600	1782 kg
	2714	19	77						
KQSN600-M14-643	1300	27	72	990	643	560	DN500	DN600	6110 kg
	2167	22	83						
KQSN600-M14-628	2600	17	75	990	628	500	DN500	DN600	6110 kg
	1236	24	70						
KQSN600-M14-608	2060	20	81	990	608	450	DN500	DN600	6110 kg
	2472	16	73						
KQSN600-M14-583	2160	52	78	990	583	400	DN500	DN600	6110 kg
	3600	41	91						
KQSN600-M14-548	4320	32	84	990	548	315	DN500	DN600	4560 kg
	1987	49	75						
KQSN600-N14-642	3312	38	89	990	642	500	DN500	DN600	6110 kg
	3974	31	86						
KQSN600-N14-627	1908	45	78	990	627	450	DN500	DN600	6110 kg
	3180	36	87						
KQSN600-N14-607	3815	29	82	990	607	400	DN500	DN600	6110 kg
	1812	41	73						
KQSN600-N14-582	3021	33	85	990	582	355	DN500	DN600	6110 kg
	3625	27	82						
KQSN600-N14-547	1710	37	76	990	547	315	DN500	DN600	4560 kg
	2850	29	84						
KQSN600-M17S-508	3420	24	82	1480	508	1000	DN500	DN600	5880 kg
	1950	54	82						
KQSN600-M17S-482	3250	42	90	1480	482	800	DN500	DN600	5880 kg
	3900	31	87						
KQSN600-M17S-460	1872	51	80	1480	460	710	DN500	DN600	4320 kg
	3120	39	89						
KQSN600-M17SJ-508	3744	30	87	990	508	280	DN500	DN600	1710 kg
	1797	47	79,4						
KQSN600-M17SJ-482	2995	37	88	990	482	250	DN500	DN600	1820 kg
	3594	28	86						
KQSN600-M17SJ-460	1725	44	78,5	990	460	200	DN500	DN600	1610 kg
	2875	32	87						
KQSN600-M17SJ-420	3450	25	85	990	420	560	DN500	DN600	4320 kg
	1656	40	77,5						
KQSN600-M17SJ-400	2760	29	86	1480	400	630	DN500	DN600	4320 kg
	3312	22	83						
KQSN600-M17SJ-380	2448	82	86	990	380	280	DN500	DN600	1710 kg
	4080	68	91,5						
KQSN600-M17SJ-360	4896	54	87	990	360	250	DN500	DN600	1820 kg
	2322	76	85						
KQSN600-M17SJ-340	3870	60	91	990	340	250	DN500	DN600	1820 kg
	4644	48	86,5						
KQSN600-M17SJ-320	2216	68	84,5	990	320	250	DN500	DN600	1820 kg
	3694	54	90						
KQSN600-M17SJ-300	4433	41	86,2	990	300	250	DN500	DN600	1820 kg
	2120	62	83						
KQSN600-M17SJ-280	3533	49	89	990	280	250	DN500	DN600	1820 kg
	4240	38	85,5						
KQSN600-M17SJ-260	2024	54	81	990	260	250	DN500	DN600	1820 kg
	3373	44	88						
KQSN600-M17SJ-240	4048	34	85	990	240	250	DN500	DN600	1820 kg
	1680	35	87						
KQSN600-M17SJ-220	2800	30	91,5	990	220	250	DN500	DN600	1820 kg
	3360	24	87						
KQSN600-M17SJ-200	1594	32	86,1	990	200	250	DN500	DN600	1820 kg
	2656	25	91						
KQSN600-M17SJ-180	3187	18	86,3	990	180	250	DN500	DN600	1820 kg
	1521	29	86						
KQSN600-M17SJ-160	2535	23	90,5	990	160	250	DN500	DN600	1820 kg

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN600-M17SJ-440	3042	17	86,2	990	440	185	DN500	DN600	1610 kg
	1455	26	85,5						
	2425	21	89						
	2910	17	85,8						
KQSN600-M17SJ-420	1388	21	84	990	420	160	DN500	DN600	1610 kg
	2314	19	87,5						
	2777	15	85						
KQSN600-M19-540	1902	37	69	990	540	355	DN500	DN600	3200 kg
	3170	32	91						
	3804	25	78						
KQSN600-M19-529	1864	36	68	990	529	355	DN500	DN600	3200 kg
	3107	31	90						
	3728	24	77						
KQSN600-M19-508	1778	33	67	990	508	315	DN500	DN600	3100 kg
	2980	29	89						
	3576	22	76						
KQSN600-M19-470	1655	28	66	990	470	250	DN500	DN600	2053 kg
	2758	24	88						
	3309	19	75						
KQSN600-N19-540	1614	36	63	990	540	315	DN500	DN600	3100 kg
	2690	31	90						
	3228	25	78						
KQSN600-N19-518	1549	33	62	990	518	280	DN500	DN600	3100 kg
	2582	29	89						
	3099	23	77						
KQSN600-N19-497	1485	31	61	990	497	250	DN500	DN600	2053 kg
	2475	26	88						
	2970	21	76						
KQSN600-N19-470	1404	27	60	990	470	250	DN500	DN600	1922 kg
	2340	24	87						
	2808	19	75						
KQSN600-M20S-460	2030	57	84	1480	460	560	DN500	DN600	4060 kg
	3372	48	90,5						
	4046	36	87						
KQSN600-M20S-440	1936	54	84	1480	440	500	DN500	DN600	4060 kg
	3226	44	90,5						
	3871	32	87						
KQSN600-M20S-425	1870	50	85,5	1480	425	450	DN500	DN600	4940 kg
	3116	41	90						
	3739	28	86,5						
KQSN600-M20S-410	1804	46	83	1480	410	400	DN500	DN600	3810 kg
	3006	38	89						
	3607	25	86						
KQSN600-M20S-395	1738	41	83	1480	395	400	DN500	DN600	3810 kg
	2897	36	87						
	3476	22	85,5						
KQSN600-M20SJ-460	1361	25	83	990	460	160	DN500	DN600	1847 kg
	2269	21	90,5						
	2723	17	87						
KQSN600-M20SJ-440	1302	24	84	990	440	160	DN500	DN600	1847 kg
	2170	19	89,5						
	2604	16	88						
KQSN600-M20SJ-425	1258	23	85	990	425	160	DN500	DN600	1847 kg
	2097	18	89						
	2516	15	88						
KQSN600-M20SJ-410	1214	21	85	990	410	132	DN500	DN600	1596 kg
	2023	17	88						
	2428	14	87						
KQSN600-M20SJ-395	1169	19	84	990	395	110	DN500	DN600	1596 kg
	1949	15	88						
	2339	13	87						
KQSN600-M27-485	1930	27	75	990	485	250	DN500	DN600	2053 kg
	3216	22	90						
	3859	15	80						
KQSN600-M27-461	1830	25	74	990	461	220	DN500	DN600	1922 kg
	3050	20	89						
	3660	14	79						
KQSN600-M27-437	1740	22	73	990	437	200	DN500	DN600	1779 kg
	2900	18	88						
	3480	12	78						
KQSN600-M27-412	1650	20	72	990	412	185	DN500	DN600	1779 kg
	2750	16	87						
	3300	11	77						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN600-N27-485	1614	26	68	990	485	220	DN500	DN600	1922 kg	
	2690	22	89							
	3228	15	79							
KQSN600-N27-466	1549	24	67	990	466	200	DN500	DN600	1779 kg	
	2582	20	88							
	3099	14	78							
KQSN600-N27-441	1469	22	66	990	441	185	DN500	DN600	1685 kg	
	2448	18	87							
	2937	12	77							
KQSN600-N27-412	1372	19	65	990	412	160	DN500	DN600	1685 kg	
	2286	16	86							
	2743	11	76							
Tên nhóm: 10										
KQSN700-M6-1040	3090	180	80,5	990	1040	2800	DN500	DN700	20000 kg	
	5150	160	89,5							
	6438	131	82,5							
KQSN700-M6-975	2772	158	80,1	990	975	2240	DN500	DN700	19500 kg	
	4620	140	89							
	5775	115	81,9							
KQSN700-M6-915	2592	135	79,2	990	915	1800	DN500	DN700	9285 kg	
	4320	120	88							
	5400	98	81							
KQSN700-M6-860	2340	118	77,4	990	860	1600	DN500	DN700	9060 kg	
	3900	105	86							
	4875	86	78,8							
KQSN700-N6-1040	2628	173	79,6	990	1040	2500	DN500	DN700	19700 kg	
	4380	154	88,5							
	5475	126	81,4							
KQSN700-N6-975	2376	151	79,2	990	975	2000	DN500	DN700	9640 kg	
	3960	134	88							
	4950	110	81							
KQSN700-N6-915	2208	129	78,3	990	915	1600	DN500	DN700	9060 kg	
	3680	115	87							
	4600	94	80							
KQSN700-N6-860	2016	113	77	990	860	1250	DN500	DN700	7818 kg	
	3360	100	85,5							
	4200	82	78,7							
KQSN700-M6J-1140	2700	118	80,1	740	1140	1600	DN500	DN700	18800 kg	
	4500	105	89							
	5625	85	81,9							
KQSN700-M6J-1040	2310	101	79,7	740	1040	1250	DN500	DN700	8660 kg	
	3850	90	88,5							
	4813	74	81,4							
KQSN700-M6J-975	2070	88	79,2	740	975	1000	DN500	DN700	8250 kg	
	3450	78	88							
	4313	64	81							
KQSN700-M6J-915	1938	75	78,3	740	915	800	DN500	DN700	6890 kg	
	3230	67	87							
	4038	55	80							
KQSN700-M6J-860	1749	66	77	740	860	630	DN500	DN700	6450 kg	
	2915	59	85,5							
	3644	48	78,7							
KQSN700-N6J-1140	2160	114	79,2	740	1140	1250	DN500	DN700	13097 kg	
	3600	101	88							
	4500	82	81							
KQSN700-N6J-1040	1965	97	78,8	740	1040	1000	DN500	DN700	16202 kg	
	3275	86	87,5							
	4094	70	80,5							
KQSN700-N6J-975	1776	84	78,3	740	975	800	DN500	DN700	14627 kg	
	2960	75	87							
	3700	61	80							
KQSN700-N6J-915	1650	72	77,4	740	915	630	DN500	DN700	14182 kg	
	2750	64	86							
	3438	52	79,1							
KQSN700-N6J-860	1500	63	75,6	740	860	560	DN500	DN700	13027 kg	
	2500	56	84							
	3125	46	77,3							
KQSN700-M6JJ-1140	2152	75	80,1	590	1140	900	DN500	DN700	12720 kg	
	3587	67	89							
	4484	54	81,9							
KQSN700-M6JJ-1040	1841	64	79,7	590	1040	630	DN500	DN700	14635 kg	
	3068	57	88,5							
	3835	47	81,4							

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN700-M6JJ-975	1650	56	79,2	590	975	500	DN500	DN700	14190 kg
	2750	50	88						
	3438	41	81						
KQSN700-M6JJ-915	1544	48	78,3	590	915	400	DN500	DN700	5270 kg
	2574	43	87						
	3218	35	80						
KQSN700-M6JJ-860	1394	43	77	590	860	315	DN500	DN700	4940 kg
	2323	38	85,5						
	2904	31	78,7						
KQSN700-N6JJ-1140	1721	72	79,2	590	1140	630	DN500	DN700	6860 kg
	2869	64	88						
	3586	52	81						
KQSN700-N6JJ-1040	1566	62	78,8	590	1040	500	DN500	DN700	6420 kg
	2610	55	87,5						
	3263	45	80,5						
KQSN700-N6JJ-975	1415	48	78,3	590	975	400	DN500	DN700	5270 kg
	2359	48	87						
	2949	39	80						
KQSN700-N6JJ-915	1315	46	77,4	590	915	315	DN500	DN700	4940 kg
	2192	41	86						
	2740	33	79,1						
KQSN700-N6JJ-860	1196	40	75,6	590	860	280	DN500	DN700	4781 kg
	1993	36	84						
	2491	30	77,3						
KQSN700-M9-936	3000	120	80	990	936	2000	DN600	DN700	9640 kg
	5000	108	89,5						
	6000	98	83						
KQSN700-M9-901	2880	112	79,5	990	901	1800	DN600	DN700	9285 kg
	4800	100	88,5						
	5760	90	82						
KQSN700-M9-869	2765	105	79	990	869	1600	DN600	DN700	9060 kg
	4608	93	87,5						
	5530	83	81						
KQSN700-M9-800	2627	91	78	990	800	1250	DN600	DN700	7818 kg
	4378	78	86						
	5253	67	80						
KQSN700-M9-752	2521	84	77	990	752	1120	DN600	DN700	7600 kg
	4202	71	84,5						
	5043	60	79						
KQSN700-N9-935	2610	114	80	990	935	1600	DN600	DN700	9060 kg
	4350	104	89						
	5220	94	83,5						
KQSN700-N9-900	2506	105	79,5	990	900	1400	DN600	DN700	8850 kg
	4176	92	88						
	5011	84	82,5						
KQSN700-N9-868	2405	97	79	990	868	1250	DN600	DN700	7818 kg
	4009	84	87						
	4811	76	81,5						
KQSN700-N9-798	2309	86	78	990	798	1000	DN600	DN700	7350 kg
	3849	72	85,5						
	4618	63	80,5						
KQSN700-N9-751	2217	79	77	990	751	900	DN600	DN700	7122 kg
	3695	65	84						
	4434	56	78,5						
KQSN700-M9J-936	2242	67	81,5	740	936	800	DN600	DN700	6890 kg
	3810	60	89,5						
	4485	55	84,5						
KQSN700-M9J-901	2153	63	82	740	901	710	DN600	DN700	6650 kg
	3588	56	88,5						
	4305	50	83,5						
KQSN700-M9J-869	2067	59	81,5	740	869	630	DN600	DN700	6450 kg
	3444	52	87,5						
	4133	46	83						
KQSN700-M9J-800	1963	51	80,5	740	800	560	DN600	DN700	5320 kg
	3272	44	86						
	3927	37	82						
KQSN700-M9J-752	1885	47	79,5	740	752	450	DN600	DN700	4990 kg
	3141	40	84,5						
	3770	34	81						
KQSN700-N9J-935	1906	64	81	740	935	710	DN600	DN700	6650 kg
	3177	58	88,5						
	3812	54	84						
	1830	59	80						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN700-N9J-900	3050	51	87	740	900	630	DN600	DN700	6450 kg
	3660	47	83						
KQSN700-N9J-868	1757	54	79	740	868	500	DN600	DN700	5160 kg
	2928	47	86						
KQSN700-N9J-798	3513	42	81,5	740	798	450	DN600	DN700	5160 kg
	1686	48	78						
KQSN700-N9J-751	2811	40	84	740	751	400	DN600	DN700	4810 kg
	3373	35	80,5						
KQSN700-M12S -740	1619	44	77	740	740	1120	DN600	DN700	7600 kg
	2698	36	82,5						
KQSN700-M12S -700	3238	31	78,5	990	700	1000	DN600	DN700	7350 kg
	2880	79	84						
KQSN700-M12S -665	4800	68	92	990	665	900	DN600	DN700	7122 kg
	5760	55	89						
KQSN700-M12S -630	2736	71	83	990	630	800	DN600	DN700	5800 kg
	4560	60	91						
KQSN700-M12S -600	5472	51	89	990	600	630	DN600	DN700	5420 kg
	2599	67	82,5						
KQSN700-M12SJ -740	4332	58	90,5	740	740	500	DN600	DN700	5160 kg
	5198	49	89						
KQSN700-M12SJ -700	2466	62	81	740	700	450	DN600	DN700	4990 kg
	4110	54	90						
KQSN700-M12SJ -665	4932	45	88	740	665	400	DN600	DN700	4810 kg
	2343	53	80						
KQSN700-M12SJ -630	3905	44	89	740	630	355	DN600	DN700	4640 kg
	4686	37	86						
KQSN700-M12SJ -600	2153	44	83	740	600	280	DN600	DN700	3840 kg
	3558	38	92						
KQSN700-M14-701	4306	31	89	990	701	1000	DN600	DN700	7350 kg
	2045	40	82,5						
KQSN700-M14-639	3409	34	91	990	639	800	DN600	DN700	5800 kg
	4090	28	88,5						
KQSN700-M14-602	1943	37	82	990	602	630	DN600	DN700	5420 kg
	3238	32	90						
KQSN700-M14-578	3886	27	87,5	990	578	560	DN600	DN700	5230 kg
	1843	35	81						
KQSN700-M14-700	3072	30	89	990	700	800	DN600	DN700	5800 kg
	3687	25	86,5						
KQSN700-M14-638	1751	30	80	990	638	710	DN600	DN700	5600 kg
	2919	25	88						
KQSN700-M14-600	3503	21	85,5	990	600	560	DN600	DN700	5230 kg
	3060	70	80						
KQSN700-M14-577	5100	57	90	990	577	500	DN600	DN700	4160 kg
	6120	49	83,5						
KQSN700-M17S -620	2938	60	79,5	990	620	800	DN600	DN700	5800 kg
	4896	47	89						
KQSN700-M17S -580	5875	39	82,5	990	580	630	DN600	DN700	5420 kg
	2627	55	79						
KQSN700-M17S -550	4378	41	88	990	550	560	DN600	DN700	5230 kg
	5253	33	81,5						
	2521	51	78						
	4202	37	86,5						
	5043	30	80,5						
	2448	71	79,5						
	4080	57	89						
	4896	47	83						
	2350	64	79						
	3917	50	88						
	4700	41	82						
	2256	57	78,5						
	3760	42	87						
	4512	34	81						
	2166	52	77,5						
	3610	37	85,5						
	4332	29	80						
	3000	56	82						
	5000	46	92						
	6000	36	85						
	2808	48	81						
	4680	40	91						
	5616	32	84						
	2661	44	79						
	4435	36	90						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN700-M17S -530	5322	28	83,5	990	530	500	DN600	DN700	4160 kg
	2564	40	78						
	4274	33	88						
	5129	27	83,5						
KQSN700-M17S -510	2466	36	76,5	990	510	450	DN600	DN700	4050 kg
	4110	31	87						
	4932	24	82						
KQSN700-M17SJ -620	2280	31	81	740	620	355	DN600	DN700	3910 kg
	3800	24	92,5						
	4560	22	84,5						
KQSN700-M17SJ -580	2132	28	80	740	580	280	DN600	DN700	3840 kg
	3554	22	91						
	4265	17	83						
KQSN700-M17SJ -550	2022	25	79	740	550	250	DN600	DN700	3590 kg
	3370	19	89,5						
	4044	16	82						
KQSN700-M17SJ -530	1949	23	78	740	530	200	DN600	DN700	1900 kg
	3248	17	89						
	3898	13	80						
KQSN700-M17SJ -510	1875	18	77	740	510	160	DN600	DN700	1782 kg
	3125	14	88,5						
	3750	12	78,5						
KQSN700-M20S -534	2100	34	84	990	534	355	DN500	DN700	3870 kg
	3500	29	91						
	4200	24	86						
KQSN700-M20S -515	2025	32	83	990	515	315	DN500	DN700	3770 kg
	3375	27	90						
	4050	22	86						
KQSN700-M20S -495	1946	29	82	990	495	280	DN500	DN700	3640 kg
	3244	25	89						
	3893	21	87						
KQSN700-M20S -475	1868	27	81	990	475	250	DN500	DN700	2975 kg
	3113	23	89						
	3736	19	86						
KQSN700-M20S -455	1789	25	80	990	455	220	DN500	DN700	2930 kg
	2982	21	88						
	3578	17	85						
KQSN700-M20SJ -534	1575	20	84	740	534	160	DN500	DN700	1762 kg
	2625	16	91						
	3150	13	88						
KQSN700-M20SJ -515	1519	18	83	740	515	132	DN500	DN700	1630 kg
	2532	15	90						
	3038	12	87						
KQSN700-M20SJ -495	1460	17	82	740	495	132	DN500	DN700	1630 kg
	2433	14	89						
	2920	11	87						
KQSN700-M20SJ -475	1404	16	81	740	475	110	DN600	DN700	1266 kg
	2335	13	89						
	2802	10	87						
KQSN700-M20SJ -455	1342	14	80	740	455	110	DN500	DN700	1266 kg
	2237	12	88						
	2684	9	87						
KQSN700-M27-571	2824	33	80	990	571	400	DN700	DN700	3980 kg
	4707	24	88,5						
	5648	20	83,5						
KQSN700-M27-547	2711	31	79,5	990	547	355	DN700	DN700	3870 kg
	4519	22	87,5						
	5422	18	82,5						
KQSN700-M27-526	2603	30	79	990	526	315	DN700	DN700	3770 kg
	4338	20	86,5						
	5206	16	81,5						
KQSN700-M27-510	2473	27	78	990	510	250	DN700	DN700	2975 kg
	4121	16	85						
	4945	12	80,5						
KQSN700-N27-570	2600	32	79,5	990	570	355	DN700	DN700	3870 kg
	4334	23	88						
	5201	19	83						
KQSN700-N27-535	2332	29	79	990	535	280	DN700	DN700	3640 kg
	3887	20	87						
	4664	16	82						
KQSN700-N27-513	2239	28	78,5	990	513	250	DN700	DN700	2975 kg
	3732	18	86						
	4478	14	81						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN700-N27-502	2149	26	77,5	990	502	220	DN700	DN700	2930 kg	
	3582	16	84,5							
	4299	12	80							
KQSN700-M27J-571	2108	18	80	740	571	185	DN700	DN700	1900 kg	
	3513	13	87,5							
	4216	11	83							
KQSN700-M27J-547	2024	17	79,5	740	547	160	DN700	DN700	1782 kg	
	3373	12	86,5							
	4047	10	82							
KQSN700-M27J-526	1943	17	79	740	526	132	DN700	DN700	1650 kg	
	3238	11	85,5							
	3885	9	81							
KQSN700-M27J-510	1845	15	78	740	510	110	DN700	DN700	1315 kg	
	3076	9	84							
	3691	7	80							
KQSN700-N27J-570	1794	18	79,5	740	570	160	DN700	DN700	1782 kg	
	2990	13	87							
	3588	11	82,5							
KQSN700-N27J-535	1722	16	79	740	535	132	DN700	DN700	1650 kg	
	2870	11	86							
	3444	9	81,5							
KQSN700-N27J-513	1653	16	78,5	740	513	110	DN700	DN700	1315 kg	
	2755	10	85							
	3307	8	80,5							
KQSN700-N27J-502	1587	15	77,5	740	502	110	DN700	DN700	1315 kg	
	2645	9	83,5							
	3174	7	79,5							
Tên nhóm: 11										
KQSN800-M12-1010	4500	83	80	740	1010	1800	DN700	DN800	19100 kg	
	7500	70	91							
	9000	55	83							
KQSN800-M12-950	4179	71	79	740	950	1600	DN700	DN800	18800 kg	
	6965	60	90							
	8357	50	82							
KQSN800-M12-890	3880	60	78	740	890	1250	DN700	DN800	8660 kg	
	6467	51	89							
	7761	43	81							
KQSN800-M12-840	3582	52	75	740	840	1000	DN700	DN800	8250 kg	
	5970	44	88							
	7164	36	81							
KQSN800-N12-1010	3780	79	79	740	1010	1600	DN700	DN800	18800 kg	
	6300	67	90,5							
	7560	54	83							
KQSN800-N12-950	3480	68	77	740	950	1250	DN700	DN800	8660 kg	
	5800	58	89,5							
	6960	50	82							
KQSN800-N12-890	3240	57	75	740	890	1000	DN700	DN800	8250 kg	
	5400	49	87							
	6480	44	81							
KQSN800-N12-840	3030	49	73	740	840	800	DN700	DN800	6890 kg	
	5050	43	85,5							
	6060	36	79							
KQSN800-M12S-775	3300	84	83	990	775	1400	DN600	DN800	8850 kg	
	5500	74	92,5							
	6600	62	89							
KQSN800-M12S-740	3180	79	81	990	740	1250	DN600	DN800	7818 kg	
	5300	69	92							
	6360	57	88							
KQSN800-M12S-721	3070	74	80	990	721	1120	DN600	DN800	7600 kg	
	5150	64	91,5							
	6140	53	87							
KQSN800-M12S-680	3000	64	80	990	680	1000	DN600	DN800	7350 kg	
	5000	58	91							
	6000	48	87							
KQSN800-M12S-640	2910	57	80	990	640	900	DN600	DN800	7122 kg	
	4850	50	90,5							
	5820	40	84							
KQSN800-M12SJ-775	2460	49	83	740	775	630	DN600	DN800	6450 kg	
	4100	44	92,5							
	4920	37	89							
KQSN800-M12SJ-740	2340	47	82,5	740	740	560	DN600	DN800	5320 kg	
	3900	42	92							
	4680	36	89							

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN800-M12SJ-721	2310	43	82	740	721	500	DN600	DN800	5160 kg
	3850	38	91,5						
	4620	32	88						
KQSN800-M12SJ-680	2280	38	81	740	680	450	DN600	DN800	4990 kg
	3800	33	91						
	4560	27	86						
KQSN800-M12SJ-640	2100	35	80	740	640	400	DN600	DN800	4810 kg
	3500	30	90,5						
	4200	24	85						
KQSN800-M13-890	3888	65	79,5	740	890	1250	DN700	DN800	8660 kg
	6480	53	90						
	7776	46	81						
KQSN800-M13-855	3720	60	79	740	855	1120	DN700	DN800	8460 kg
	6200	49	89						
	7440	42	80						
KQSN800-M13-820	3600	56	78,5	740	820	1000	DN700	DN800	8250 kg
	6000	45	88						
	7200	39	79						
KQSN800-M13-788	3456	52	78	740	788	900	DN700	DN800	6910 kg
	5760	42	87						
	6912	37	78,5						
KQSN800-N13-890	3390	64	82	740	890	1000	DN700	DN800	8250 kg
	5650	53	92						
	6780	45	84						
KQSN800-N13-855	3162	58	79,5	740	855	900	DN700	DN800	6910 kg
	5270	47	91						
	6324	40	81						
KQSN800-N13-820	3060	56	79	740	820	800	DN700	DN800	6890 kg
	5100	45	88						
	6120	38	80						
KQSN800-N13-788	2938	51	78	740	788	710	DN700	DN800	6650 kg
	4896	41	87						
	5875	34	78,5						
KQSN800-M14-862	4380	98	80,5	990	862	2500	DN700	DN800	14000 kg
	7300	85	89,5						
	8760	76	83,5						
KQSN800-M14-818	4205	90	80	990	818	2000	DN700	DN800	9640 kg
	7008	77	88,5						
	8410	68	82,5						
KQSN800-M14-765	4037	79	79,5	990	765	1600	DN700	DN800	9060 kg
	6728	66	87,5						
	8073	56	81,5						
KQSN800-M14-720	3535	73	78,5	990	720	1400	DN700	DN800	8850 kg
	6391	59	86						
	7670	49	80,5						
KQSN800-M14-666	3681	64	77,5	990	666	1120	DN700	DN800	7600 kg
	6136	50	84,5						
	7363	40	79,5						
KQSN800-N14-860	3840	96	80	990	860	2000	DN700	DN800	9640 kg
	6400	83	88,5						
	7680	74	83						
KQSN800-N14-817	3686	86	79,5	990	817	1600	DN700	DN800	9060 kg
	6144	73	87,5						
	7373	64	82						
KQSN800-N14-763	3539	79	79	990	763	1400	DN700	DN800	8850 kg
	5898	66	86,5						
	7078	56	81						
KQSN800-N14-718	3397	72	78	990	718	1250	DN700	DN800	7818 kg
	5662	58	85						
	6795	48	80						
KQSN800-N14-664	3261	64	77	990	664	1000	DN700	DN800	7350 kg
	5436	50	83,5						
	6523	40	78						
KQSN800-M14J-862	3274	55	80,5	740	862	900	DN700	DN800	6910 kg
	5457	47	89						
	6548	42	84,2						
KQSN800-M14J-818	3143	50	80	740	818	800	DN700	DN800	6890 kg
	5238	43	88						
	6286	38	83,2						
KQSN800-M14J-765	3017	44	79,5	740	765	710	DN700	DN800	6650 kg
	5029	37	87						
	6034	31	82,2						
	2866	41	78,5						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN800-M14J-720	4777	33	85,5	740	720	560	DN700	DN800	5320 kg
	5733	27	81,2						
KQSN800-M14J-666	2752	36	77,5	740	666	500	DN700	DN800	5160 kg
	4586	28	84						
KQSN800-N14J-860	5503	22	80,2	740	860	800	DN700	DN800	6890 kg
	2783	54	80						
KQSN800-N14J-817	4638	46	88	740	817	710	DN700	DN800	6650 kg
	5566	41	83						
KQSN800-N14J-763	2672	48	79,5	740	763	560	DN700	DN800	5320 kg
	4453	41	87						
KQSN800-N14J-718	5343	36	82	740	718	500	DN700	DN800	5160 kg
	2565	44	79						
KQSN800-N14J-664	4274	37	86	740	664	400	DN700	DN800	5645 kg
	5129	31	81						
KQSN800-M17S-650	2462	40	78	990	650	1120	DN700	DN800	7600 kg
	4103	32	84,5						
KQSN800-M17S-625	4924	27	80	990	625	1000	DN700	DN800	7350 kg
	2364	36	77						
KQSN800-M17S-600	3939	28	83	990	600	900	DN700	DN800	7122 kg
	4727	22	78						
KQSN800-M17S-575	3600	60	86	990	575	800	DN700	DN800	5800 kg
	6000	53	92						
KQSN800-M17S-550	7200	40	89	990	550	710	DN700	DN800	5600 kg
	3462	55	85						
KQSN800-M17SJ-650	5769	49	91,5	740	650	450	DN700	DN800	4990 kg
	6923	37	88						
KQSN800-M17SJ-625	3323	51	84	740	625	400	DN700	DN800	4810 kg
	5538	45	91						
KQSN800-M17SJ-600	6646	34	88	740	600	355	DN700	DN800	4640 kg
	3185	47	83						
KQSN800-M17SJ-575	5308	41	90	740	575	315	DN700	DN800	3910 kg
	6369	31	88						
KQSN800-M17SJ-550	3046	43	82	740	550	280	DN700	DN800	3840 kg
	5077	38	89						
KQSN800-M20-707	6092	29	87	990	707	1000	DN700	DN800	7350 kg
	2691	34	86						
KQSN800-M20-673	4485	30	92	990	673	900	DN700	DN800	7122 kg
	5382	22	89						
KQSN800-M20-633	2587	31	85	990	633	800	DN700	DN800	5800 kg
	4312	27	91,5						
KQSN800-M20-598	5175	21	88	990	598	630	DN700	DN800	5420 kg
	2484	29	84						
KQSN800-N20-706	4140	25	91	990	706	800	DN700	DN800	5800 kg
	4968	19	88						
KQSN800-N20-672	2380	26	83	990	672	710	DN700	DN800	5600 kg
	3967	23	90						
KQSN800-N20-631	4761	17	88	990	631	630	DN700	DN800	5420 kg
	2277	24	82						
KQSN800-N20-597	3795	21	89	990	597	560	DN700	DN800	5230 kg
	4554	16	87						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN800-M20J-707	5924	21	78,5	740	707	450	DN700	DN800	4990 kg
	2960	32	79,5						
	4933	25	91						
	5920	21	83						
KQSN800-M20J-673	2841	30	79	740	673	400	DN700	DN800	4810 kg
	4736	22	90						
	5683	18	82						
KQSN800-M20J-633	2728	27	78	740	633	355	DN700	DN800	4640 kg
	4547	20	88,5						
	5456	16	81						
KQSN800-M20J-598	2592	25	77	740	598	280	DN700	DN800	3840 kg
	4241	17	85,5						
	5183	13	80						
KQSN800-N20J-706	2503	30	79,5	740	706	355	DN700	DN800	4640 kg
	4171	22	88,5						
	5005	18	82						
KQSN800-N20J-672	2402	28	79	740	672	315	DN700	DN800	3910 kg
	4004	20	87,5						
	4805	16	81						
KQSN800-N20J-631	2305	26	78	740	631	280	DN700	DN800	3840 kg
	3844	18	86						
	4613	14	80						
KQSN800-N20J-597	2214	24	77	740	597	250	DN700	DN800	3730 kg
	3690	15	84,5						
	4428	11	78						
KQSN800-M20S-605	3168	46	84	990	605	710	DN600	DN800	5600 kg
	5280	38	92						
	6336	33	87						
KQSN800-M20S-575	3011	41	83	990	575	560	DN600	DN800	5230 kg
	5018	34	90						
	6022	28	87						
KQSN800-M20S-545	2854	36	82	990	545	500	DN600	DN800	4160 kg
	4756	30	89						
	5707	24	87						
KQSN800-M20S-525	2749	33	81	990	525	450	DN600	DN800	4050 kg
	4582	28	89						
	5498	22	87						
KQSN800-M20S-505	2644	30	80	990	505	400	DN600	DN800	3980 kg
	4407	26	88						
	5288	21	86						
KQSN800-M20SJ-605	2370	26	84	740	605	315	DN600	DN800	3840 kg
	3950	22	92						
	4740	19	89						
KQSN800-M20SJ-575	2280	23	83	740	575	250	DN600	DN800	3730 kg
	3800	19	90						
	4560	15	87						
KQSN800-M20SJ-545	2160	20	82	740	545	220	DN600	DN800	3590 kg
	3600	17	89						
	4320	14	87						
KQSN800-M20SJ-525	2057	18	81	740	525	185	DN600	DN800	1900 kg
	3428	15	89						
	4114	12	87						
KQSN800-M20SJ-505	1978	16	80	740	505	160	DN600	DN800	1782 kg
	3297	13	88						
	3956	10	86						
KQSN800-M24-666	4199	31	80	740	666	630	DN800	DN800	6450 kg
	6999	24	89,5						
	8399	18	83						
KQSN800-M24-651	4031	29	79,5	740	651	560	DN800	DN800	5320 kg
	6719	22	88,5						
	8063	17	82						
KQSN800-M24-637	3870	27	79	740	637	500	DN800	DN800	5160 kg
	6450	21	87,5						
	7740	16	81						
KQSN800-M24-625	3677	26	78	740	625	450	DN800	DN800	4990 kg
	6128	19	86						
	7353	15	80						
KQSN800-M24-618	3530	25	77	740	618	400	DN700	DN800	4810 kg
	5883	18	84,5						
	7059	14	79						
KQSN800-N24-665	3575	30	80	740	665	500	DN800	DN800	5160 kg
	5958	23	88,5						
	7150	18	82,5						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN800-N24-650	3432	29	79,5	740	650	450	DN800	DN800	4990 kg	
	5720	21	87,5							
	6864	16	81,5							
KQSN800-N24-636	3295	28	79	740	636	400	DN800	DN800	4810 kg	
	5491	20	86,5							
	6589	15	80,5							
KQSN800-N24-622	3163	27	78	740	622	400	DN800	DN800	4810 kg	
	5271	19	85							
	6326	14	79,5							
KQSN800-M28-567	3888	39	80	990	567	710	DN700	DN800	5600 kg	
	6480	30	89,5							
	7776	25	83							
KQSN800-M28-538	3732	37	79,5	990	538	630	DN700	DN800	5420 kg	
	6221	27	88,5							
	7465	22	82							
KQSN800-M28-508	3583	35	79	990	508	560	DN700	DN800	5230 kg	
	5972	24	87,5							
	7166	19	81							
KQSN800-M28-472	3404	32	78	990	472	450	DN700	DN800	4050 kg	
	5673	20	86							
	6808	16	80							
KQSN800-M28-448	3268	29	77	990	448	400	DN700	DN800	3980 kg	
	5446	17	84,5							
	6536	13	79							
KQSN800-N28-566	2981	33	80	990	566	560	DN700	DN800	5230 kg	
	4968	24	88,5							
	5962	16	82,5							
KQSN800-N28-537	2862	30	79,5	990	537	500	DN700	DN800	4160 kg	
	4769	21	87,5							
	5723	14	81,5							
KQSN800-N28-507	2747	28	79	990	507	450	DN700	DN800	4050 kg	
	4579	19	86,5							
	5494	13	80,5							
KQSN800-N28-471	2637	26	78	990	471	400	DN700	DN800	3980 kg	
	4395	17	85							
	5274	12	79,5							
KQSN800-M28J-567	2906	22	80	740	567	280	DN700	DN800	3840 kg	
	4844	17	89							
	5812	14	83							
KQSN800-M28J-538	2790	21	79,5	740	538	250	DN700	DN800	3730 kg	
	4650	15	88							
	5580	12	82							
KQSN800-M28J-508	2678	19	79	740	508	220	DN700	DN800	3590 kg	
	4464	13	87							
	5357	11	81							
KQSN800-M28J-472	2544	18	78	740	472	185	DN700	DN800	3400 kg	
	4241	11	85,5							
	5089	9	80							
KQSN800-M28J-448	2443	16	77	740	448	185	DN700	DN800	3400 kg	
	4071	9	84							
	4885	7	79							
KQSN800-N28J-566	2228	18	80	740	566	250	DN700	DN800	3730 kg	
	3713	13	88							
	4456	9	82							
KQSN800-N28J-537	2139	17	79,5	740	537	220	DN700	DN800	3590 kg	
	3565	12	87							
	4278	8	81							
KQSN800-N28J-507	2053	16	79	740	507	200	DN700	DN800	3500 kg	
	3422	11	86							
	4107	7	80							
KQSN800-N28J-471	1971	15	78	740	471	185	DN700	DN800	3500 kg	
	3285	9	84,5							
	3942	7	79							
Tên nhóm: 12										
KQSN900-M12S-874	4800	110	83,5	990	874	2500	DN700	DN900	19700 kg	
	8000	93	92							
	9600	78	88,5							
KQSN900-M12S-826	4704	98	83	990	826	2240	DN700	DN900	9553 kg	
	7840	82	91							
	9408	66	88							
KQSN900-M12S-800	4620	94	83	990	800	2000	DN700	DN900	9640 kg	
	7700	78	90							
	9240	67	88,3							

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN900-M12S-778	4608	87	83	990	778	1800	DN700	DN900	9285 kg
	7680	72	90						
	9216	60	88						
KQSN900-M12S-730	4320	76	82	990	730	1600	DN700	DN900	9060 kg
	7200	65	88						
	8640	51	84						
KQSN900-M12SJ-874	3600	66	82	740	874	1120	DN700	DN900	8460 kg
	6000	53	92						
	7200	47	89						
KQSN900-M12SJ-850	3501	60	83	740	850	1000	DN700	DN900	8250 kg
	5835	50	91						
	7002	42	89						
KQSN900-M12SJ-828	3411	53	83	740	828	900	DN700	DN900	6910 kg
	5684	44	90						
	6821	37	87,5						
KQSN900-M12SJ-778	3205	44	50	740	778	800	DN700	DN900	6890 kg
	5341	41	89						
	6409	37	89						
KQSN900-M12SJ-730	3007	40	78	740	730	710	DN700	DN900	6650 kg
	5011	37	88						
	6014	27	83,5						
KQSN900-M17S-732	4920	78	82	990	732	1800	DN700	DN900	9285 kg
	8200	64	91						
	9840	50	85						
KQSN900-M17S-684	4313	68	81	990	684	1400	DN700	DN900	8850 kg
	7189	56	90						
	8627	43	82,5						
KQSN900-M17S-649	3878	61	79	990	649	1120	DN700	DN900	7600 kg
	6464	50	89						
	7757	39	82						
KQSN900-M17S-625	3602	56	78	990	625	1000	DN700	DN900	7350 kg
	6003	46	88						
	7204	36	81,5						
KQSN900-M17S-602	3335	52	77	990	602	900	DN700	DN900	7122 kg
	5558	43	87						
	6670	34	81						
KQSN900-M17SJ-732	3677	44	81	740	732	800	DN700	DN900	6890 kg
	6200	36	90						
	73505	28	82,5						
KQSN900-M17SJ-684	3225	38	80	740	684	630	DN700	DN900	6450 kg
	5375	31	89						
	6450	25	82						
KQSN900-M17SJ-649	2898	34	79	740	649	500	DN700	DN900	5160 kg
	4831	28	88						
	5797	22	81,5						
KQSN900-M17SJ-625	2692	31	78	740	625	450	DN700	DN900	4990 kg
	4487	26	87						
	5384	20	80						
KQSN900-M17SJ-602	3492	29	77	740	602	400	DN700	DN900	4810 kg
	4154	24	86						
	4985	19	78,5						
KQSN900-M20S-696	4636	60	83	990	696	1400	DN800	DN900	8850 kg
	7727	48	91						
	9272	43	88						
KQSN900-M20S-665	4429	56	83	990	665	1250	DN800	DN900	7818 kg
	7382	45	90,5						
	8858	40	89,5						
KQSN900-M20S-645	4296	53	83,5	990	645	1120	DN800	DN900	7600 kg
	7160	41	90,5						
	8592	37	88						
KQSN900-M20S-620	4130	49	82	990	620	1000	DN800	DN900	7350 kg
	6883	39	89						
	8260	35	87						
KQSN900-M20S-595	3963	45	82	990	595	900	DN700	DN900	7122 kg
	6605	36	88						
	7926	33	86						
KQSN900-M20SJ-696	3465	32	83	740	696	560	DN700	DN900	5320 kg
	5776	27	91						
	6931	21	88						
KQSN900-M20SJ-665	3311	30	83	740	665	500	DN700	DN900	5160 kg
	5518	25	90,5						
	6622	19	89,5						
	3211	28	83,5						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN900-M20SJ-645	5352	23	90,5	740	645	450	DN700	DN900	4990 kg
	6422	17	88						
KQSN900-M20SJ-620	3087	26	82	740	620	400	DN700	DN900	4810 kg
	5145	22	89						
KQSN900-M20SJ-595	6174	16	87	740	595	355	DN700	DN900	4640 kg
	2962	24	82						
KQSN900-M23-868	4937	20	88	740	868	1400	DN800	DN900	8850 kg
	5924	15	86						
KQSN900-M23-818	6000	52	80,5	740	818	1250	DN800	DN900	8660 kg
	10000	40	91						
KQSN900-M23-778	12000	36	84,5	740	778	1120	DN800	DN900	8460 kg
	5760	48	80						
KQSN900-M23-736	9600	37	90	740	736	1000	DN800	DN900	8250 kg
	11520	32	83,5						
KQSN900-M23-680	5530	44	79,5	740	680	900	DN800	DN900	6910 kg
	9216	34	89						
KQSN900-N23-866	11059	28	82,5	740	866	1250	DN800	DN900	8660 kg
	5253	40	78,5						
KQSN900-N23-817	8755	30	87,5	740	817	1120	DN800	DN900	8460 kg
	10506	24	81,5						
KQSN900-N23-777	5043	36	77,5	740	777	1000	DN800	DN900	8250 kg
	8405	26	86						
KQSN900-N23-735	10086	20	80,5	740	735	900	DN800	DN900	6910 kg
	5100	50	80						
KQSN900-N23-680	8500	40	90	740	680	710	DN800	DN900	6650 kg
	10200	34	84						
KQSN900-M23J-868	4896	47	79,4	585	868	710	DN800	DN900	7010 kg
	8160	37	89						
KQSN900-M23J-818	9792	31	83	585	818	630	DN800	DN900	6860 kg
	4700	43	79						
KQSN900-M23J-778	7834	34	88	585	778	560	DN800	DN900	6620 kg
	9400	27	82						
KQSN900-M23J-736	4512	40	78	585	736	500	DN800	DN900	6420 kg
	7520	30	86,5						
KQSN900-M23J-680	9024	24	81	585	680	450	DN800	DN900	5470 kg
	4332	36	77						
KQSN900-N23J-866	7219	26	85	585	866	630	DN800	DN900	6860 kg
	8663	20	79						
KQSN900-N23J-817	4740	33	80,5	585	817	560	DN800	DN900	6620 kg
	7900	25	88						
KQSN900-N23J-777	9480	23	84	585	777	500	DN800	DN900	6420 kg
	4550	30	80						
KQSN900-N23J-735	7584	23	87	585	735	450	DN800	DN900	5470 kg
	9101	20	83						
KQSN900-N23J-680	4368	28	79,5	585	680	400	DN800	DN900	5270 kg
	7281	21	86						
KQSN900-M27-813	8737	18	82	740	813	900	DN900	DN900	6910 kg
	4150	25	78,5						
KQSN900-M27-781	6917	19	84,5	740	781	800	DN900	DN900	6890 kg
	8300	15	81						

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN900-M27-750		10783	20	82,5	740	750	710	DN900	DN900	6650 kg
		5176	32	79,5						
		8626	22	87,5						
		10351	18	81,5						
KQSN900-M27-718		4917	31	78,5	740	718	630	DN900	DN900	6450 kg
		8195	20	86						
		9834	15	80,5						
KQSN900-M27-685		4720	29	77,5	740	685	560	DN900	DN900	5320 kg
		7867	18	84,5						
		9440	13	79,5						
KQSN900-N27-812		4800	35	80	740	812	710	DN900	DN900	6650 kg
		8000	25	88,5						
		9600	21	83						
KQSN900-N27-780		4608	33	79,5	740	780	630	DN900	DN900	6450 kg
		7680	23	87,5						
		9216	19	82						
KQSN900-N27-749		4424	31	79	740	749	560	DN900	DN900	5320 kg
		7373	21	86,5						
		8847	16	81						
KQSN900-N27-716		4247	30	78	740	716	500	DN900	DN900	5160 kg
		7078	19	85						
		8493	14	80						
KQSN900-N27-683		4077	28	77	740	683	450	DN900	DN900	4990 kg
		6795	17	83,5						
		8154	12	78						
KQSN900-M27J-813		4437	23	80,5	585	813	450	DN900	DN900	5470 kg
		7394	16	89						
		8873	14	83						
KQSN900-M27J-781		4259	22	80	585	781	400	DN900	DN900	5270 kg
		7099	15	88						
		8518	13	82						
KQSN900-M27J-750		4089	21	79,5	585	750	355	DN900	DN900	5090 kg
		6815	14	87						
		8178	11	81						
KQSN900-M27J-718		3884	20	78,5	585	718	315	DN900	DN900	4940 kg
		6474	13	85,5						
		7769	9	80						
KQSN900-M27J-685		3729	19	77,5	585	685	280	DN900	DN900	4781 kg
		6215	11	84						
		7458	7	79						
KQSN900-N27J-812		3792	22	80	585	812	355	DN900	DN900	5090 kg
		6320	16	88						
		7584	13	83						
KQSN900-N27J-780		3640	21	79,5	585	780	315	DN900	DN900	4940 kg
		6067	14	87						
		7281	12	82						
KQSN900-N27J-749		3495	19	79	585	749	280	DN900	DN900	4781 kg
		5825	13	86						
		6989	10	81						
KQSN900-N27J-716		3355	19	78	585	716	250	DN900	DN900	4620 kg
		5592	12	84,5						
		6710	8	80						
KQSN900-N27J-683		3221	18	77	585	683	250	DN900	DN900	4620 kg
		5368	11	83						
		6441	7	78						
Tên nhóm: 13										
KQSN1000-M12S-1020		5610	87	84	740	1020	2240	DN800	DN1000	20700 kg
		9350	75	92						
		11220	62	89						
KQSN1000-M12S-985		5418	81	83	740	985	2000	DN800	DN1000	19400 kg
		9030	69	91,5						
		10836	57	88,6						
KQSN1000-M12S-950		5226	76	82,5	740	950	2000	DN800	DN1000	19400 kg
		8710	64	91						
		10452	55	88,4						
KQSN1000-M12S-900		4950	70	81,5	740	900	1600	DN800	DN1000	8785 kg
		8250	58	90						
		9900	51	88,3						
KQSN1000-M12S-850		4674	62	80,5	740	850	1600	DN800	DN1000	8785 kg
		7790	54	89						
		9348	47	88,2						
KQSN1000-M12SJ-1020		4500	55	84	590	1020	1250	DN800	DN1000	9095 kg
		7500	49	92						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN1000-M12SJ-985	9000	43	90,2	590	985	1120	DN800	DN1000	8890 kg
	4344	51	83						
	7240	45	91,5						
	8688	38	90						
KQSN1000-M12SJ-950	4188	46	82,5	590	950	1000	DN800	DN1000	8620 kg
	6980	40	91,2						
	8376	35	89,6						
	3966	43	81						
KQSN1000-M12SJ-900	6610	37	90,6	590	900	900	DN800	DN1000	8430 kg
	7932	32	89,3						
	3744	39	80,5						
	6240	33	89,5						
KQSN1000-M12SJ-850	7488	28	88	590	850	710	DN800	DN1000	7010 kg
	8160	69	80						
	13600	57	92						
	17000	44	85,2						
KQSN1000-M14-1160	1600	39	84,3	590	1160	2500	DN900	DN1000	25200 kg
	7680	62	79,2						
	12800	51	91						
	7200	57	77,9						
KQSN1000-M14-1125	12000	47	89,5	590	1125	2240	DN900	DN1000	24400 kg
	15000	36	82,9						
	6780	52	75,7						
	11300	43	87						
KQSN1000-M14-1090	14125	33	80,6	590	1090	2000	DN900	DN1000	24000 kg
	6480	46	73,1						
	10800	38	84						
	13500	29	77,8						
KQSN1000-M14-1060	6840	65	79,2	590	1060	1800	DN900	DN1000	23300 kg
	11400	54	91						
	14250	42	84,3						
	6600	62	78,3						
KQSN1000-M14-1030	11000	51	90	590	1030	1600	DN900	DN1000	20000 kg
	13750	39	83,3						
	6360	57	77,4						
	10600	47	89						
KQSN1000-N14-1160	13250	36	82,4	590	1160	2240	DN900	DN1000	24400 kg
	6150	52	76,6						
	10250	43	88						
	12813	33	81,5						
KQSN1000-N14-1125	5940	46	75,7	590	1060	1400	DN900	DN1000	19600 kg
	9900	38	87						
	12375	29	80,6						
	6777	47	79,2						
KQSN1000-N14-1090	11295	39	91	490	1030	1400	DN900	DN1000	19600 kg
	14119	30	84,3						
	6378	42	78,3						
	10630	35	90						
KQSN1000-M14J-1160	13288	27	83,3	490	1125	2000	DN900	DN1000	24500 kg
	5980	41	77						
	9966	34	88,5						
	12458	26	81,9						
KQSN1000-M14J-1125	5631	36	74,8	490	1090	1250	DN900	DN1000	19500 kg
	9385	30	86						
	11731	23	79,6						
	5382	31	72,2						
KQSN1000-M14J-1090	8970	26	83	490	1060	1120	DN900	DN1000	18600 kg
	11213	20	76,9						
	5681	45	78,3						
	9468	37	90						
KQSN1000-M14J-1060	11835	28	83,3	490	1160	1250	DN900	DN1000	19500 kg
	5482	42	77,4						
	9136	35	89						
	11420	27	82,4						
KQSN1000-N14J-1160	5282	40	76,6	490	1030	900	DN900	DN1000	8820 kg
	8804	33	88						
	11005	25	81,5						
	5108	36	75,7						
KQSN1000-N14J-1125	8513	30	87	490	1090	1120	DN900	DN1000	18600 kg
	10641	23	80,6						
	4933	31	74,8						
	8222	26	86						
KQSN1000-N14J-1030	10278	20	79,6	490	1060	1000	DN900	DN1000	18100 kg
KQSN1000-N14J-1030				490	1030	800	DN900	DN1000	8610 kg

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN1000-M17S-855	7840	53	90	740	855	1600	DN800	DN1000	8785 kg
	9800	49	91,5						
	11760	38	88						
KQSN1000-M17S-830	7611	50	89,5	740	830	1600	DN800	DN1000	8785 kg
	9500	46	91						
	11400	36	88,5						
KQSN1000-M17S-800	7360	47	89	740	800	1400	DN800	DN1000	8850 kg
	9200	43	90,5						
	11040	34	89						
KQSN1000-M17S-780	6960	44	89	740	780	1250	DN800	DN1000	8660 kg
	8700	40	90						
	10440	32	88,5						
KQSN1000-M17S-750	6720	41	88,5	740	750	1120	DN800	DN1000	8460 kg
	8400	37	90						
	10080	30	87						
KQSN1000-M17SJ-855	6240	34	89,5	590	855	800	DN800	DN1000	8200 kg
	7800	31	91,5						
	9360	28	89						
KQSN1000-M17SJ-830	6000	32	89	590	830	800	DN800	DN1000	8200 kg
	7500	28	91						
	9000	27	89,5						
KQSN1000-M17SJ-800	5760	30	89	590	800	710	DN800	DN1000	7010 kg
	7200	28	90,5						
	8640	26	88						
KQSN1000-M17SJ-780	5600	28	88,5	590	780	630	DN800	DN1000	6860 kg
	7000	26	90						
	8400	23	87,5						
KQSN1000-M17SJ-750	5376	24	88,5	590	750	560	DN800	DN1000	6620 kg
	6720	23	90						
	8064	20	87,5						
KQSN1000-M20-1038	8111	45	80,5	585	1038	1800	DN900	DN1000	23300 kg
	13518	39	91,5						
	16222	34	84,5						
KQSN1000-M20-998	7786	42	80	585	998	1600	DN900	DN1000	20000 kg
	12977	35	90,5						
	15573	30	83,5						
KQSN1000-M20-961	7475	38	79,5	585	961	1400	DN900	DN1000	19600 kg
	12458	32	89,5						
	14950	27	82,5						
KQSN1000-M20-934	7101	35	78,5	585	934	1250	DN900	DN1000	9095 kg
	11835	28	88						
	14202	23	81,5						
KQSN1000-M20-898	6817	32	77,5	585	898	1000	DN900	DN1000	8620 kg
	11362	25	86,5						
	13634	20	80,5						
KQSN1000-N20-1036	6900	42	80	585	1036	1400	DN900	DN1000	19600 kg
	11500	35	91						
	13800	30	84						
KQSN1000-N20-996	6624	39	79,5	585	996	1250	DN900	DN1000	9095 kg
	11040	32	90						
	13248	27	83						
KQSN1000-N20-960	6359	36	79	585	960	1120	DN900	DN1000	8890 kg
	10598	29	89						
	12718	23	82						
KQSN1000-N20-933	6105	34	78	585	933	1000	DN900	DN1000	8620 kg
	10174	27	87,5						
	12209	21	81						
KQSN1000-N20-897	5860	32	77	585	897	900	DN900	DN1000	8430 kg
	9767	24	86						
	11721	19	79						
KQSN1000-M20J-1038	6797	32	80,5	490	1038	1120	DN900	DN1000	18600 kg
	11328	27	90,5						
	13594	24	84						
KQSN1000-M20J-998	6525	29	80	490	998	1000	DN900	DN1000	18100 kg
	10875	25	89,5						
	13050	21	83						
KQSN1000-M20J-961	6264	27	79,5	490	961	800	DN900	DN1000	8610 kg
	10440	22	88,5						
	12528	19	82						
KQSN1000-M20J-934	5951	24	78,5	490	934	710	DN900	DN1000	8375 kg
	9918	20	87						
	11902	16	81						
	5713	22	77,5						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN1000-M20J-898	9521	18	85,5	490	898	630	DN900	DN1000	8150 kg
	11425	14	80						
KQSN1000-N20J-1036	5782	30	80	490	1036	800	DN900	DN1000	8610 kg
	9637	25	89,5						
KQSN1000-N20J-996	11564	21	84	490	996	710	DN900	DN1000	8375 kg
	5551	27	79,5						
KQSN1000-N20J-960	9252	23	88,5	490	960	630	DN900	DN1000	8150 kg
	11102	19	83						
KQSN1000-N20J-933	5329	25	79	490	933	560	DN900	DN1000	7915 kg
	8881	20	87,5						
KQSN1000-N20J-897	10658	16	82	490	897	500	DN900	DN1000	6840 kg
	5116	24	78						
KQSN1000-M20S-888	8526	19	86	740	888	1800	DN900	DN1000	19100 kg
	10231	15	81						
KQSN1000-M20S-845	4911	22	77	740	845	1600	DN900	DN1000	8785 kg
	8185	17	84,5						
KQSN1000-M20S-820	9822	13	79	740	820	1400	DN900	DN1000	8850 kg
	7250	52	82						
KQSN1000-M20S-785	12083	43	91	740	785	1250	DN900	DN1000	8660 kg
	14500	35	87,5						
KQSN1000-M20S-760	6899	49	82	740	760	1120	DN900	DN1000	8460 kg
	11499	39	90,5						
KQSN1000-M20SJ-888	13799	32	87	590	888	900	DN900	DN1000	8430 kg
	6695	46	81,5						
KQSN1000-M20SJ-845	11158	36	89,5	590	845	800	DN900	DN1000	8200 kg
	13390	29	87						
KQSN1000-M20SJ-820	6409	43	81	590	820	710	DN900	DN1000	7010 kg
	10682	33	88,5						
KQSN1000-M20SJ-785	12818	27	86	590	785	630	DN900	DN1000	6860 kg
	6205	29	81						
KQSN1000-M20SJ-760	10342	31	88	590	760	560	DN900	DN1000	6620 kg
	12410	25	85						
KQSN1000-M27-880	5780	34	81	585	880	1000	DN1000	DN1000	8620 kg
	9634	28	91						
KQSN1000-M27-855	11561	23	87,5	585	855	900	DN1000	DN1000	8430 kg
	5504	32	80,5						
KQSN1000-M27-828	9168	25	90	585	828	800	DN1000	DN1000	8200 kg
	11002	21	87,5						
KQSN1000-M27-792	5338	30	80	585	792	710	DN1000	DN1000	7010 kg
	8896	24	89,5						
KQSN1000-M27-756	10675	20	87,5	585	756	630	DN1000	DN1000	6860 kg
	5110	28	78,5						
KQSN1000-N27-818	8517	22	89	585	818	630	DN1000	DN1000	6860 kg
	10220	18	88						
KQSN1000-N27-788	4948	26	79	585	788	560	DN1000	DN1000	6620 kg
	8246	20	88						
KQSN1000-N27-738	9895	16	87	585	738	500	DN1000	DN1000	6420 kg
	6948	34	80,5						
KQSN1000-M27J-880	11580	24	90	490	880	630	DN1000	DN1000	8150 kg
	13896	20	84						
KQSN1000-M27J-855	6670	33	80	490	855	900	DN1000	DN1000	8430 kg
	11117	23	89						
KQSN1000-M27J-828	13340	18	83	490	828	800	DN1000	DN1000	8200 kg
	6480	32	80,5						
KQSN1000-M27J-792	10800	21	88	490	792	710	DN1000	DN1000	7010 kg
	12960	17	84						
KQSN1000-M27J-756	6221	30	80	490	756	630	DN1000	DN1000	6860 kg
	10368	19	87						
KQSN1000-N27-818	12442	15	84	490	818	630	DN1000	DN1000	6860 kg
	5972	28	79,5						
KQSN1000-N27-788	9953	18	86	490	788	560	DN1000	DN1000	6620 kg
	11944	13	82						
KQSN1000-N27-738	5508	29	80	490	738	500	DN1000	DN1000	6420 kg
	9180	19	89,5						
KQSN1000-M27J-880	11016	15	83	490	880	630	DN1000	DN1000	8150 kg
	5288	28	79,5						
KQSN1000-M27J-855	8813	18	88	490	855	900	DN1000	DN1000	8430 kg
	10575	14	82						
KQSN1000-M27J-828	5076	27	79	490	828	800	DN1000	DN1000	8200 kg
	8460	16	86,5						
KQSN1000-M27J-792	10152	12	81	490	792	710	DN1000	DN1000	7010 kg
	5820	24	80,5						
KQSN1000-M27J-756	9699	17	89	490	756	630	DN1000	DN1000	6860 kg
	11944	13	82						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN1000-M27J-855	11639	14	83	490	855	560	DN1000	DN1000	7915 kg
	5587	23	80						
	9311	16	87,5						
	11174	13	82						
KQSN1000-M27J-828	5428	22	80,5	490	828	500	DN1000	DN1000	6840 kg
	9046	15	89						
	10855	12	83						
	5211	21	80						
KQSN1000-M27J-792	8684	14	87,5	490	792	450	DN1000	DN1000	6610 kg
	10421	10	82						
	5002	20	79,5						
	8337	12	86						
KQSN1000-M27J-756	10004	9	81	490	756	400	DN100	DN1000	6420 kg
	4614	20	80						
	7689	13	88,5						
	9227	11	83						
KQSN1000-N27J-818	4429	20	79,5	490	818	400	DN1000	DN1000	6420 kg
	7382	12	87						
	8858	10	82						
	4252	19	79						
KQSN1000-N27J-788	7086	11	85	490	788	355	DN1000	DN1000	6190 kg
	8504	9	81						
	4252	19	79						
	7086	11	85						
KQSN1000-N27J-738	8504	9	81	490	738	315	DN1000	DN1000	5530 kg
	4252	19	79						
	7086	11	85						
	8504	9	81						
Tên nhóm: 14									
KQSN1100-M29-800	8352	27	76	590	800	1120	DN1000	DN1100	8890 kg
	13920	22	90						
	16704	19	84						
	7992	25	75						
KQSN1100-M29-765	13320	20	89	590	765	1000	DN1000	DN1100	8620 kg
	15984	17	83						
	6960	20	75						
	11600	15	90						
KQSN1100-M29J-800	13920	12	84	490	800	630	DN1000	DN1100	8150 kg
	6660	18	73						
	11100	14	89						
	13320	11	83						
KQSN1100-M29J-765	13320	11	83	490	765	560	DN1000	DN1100	7915 kg
	13320	11	83						
	13320	11	83						
	13320	11	83						
Tên nhóm: 15									
KQSN1200-M12S-1140	7920	106	83,3	740	1140	4000	DN1000	DN1200	29200 kg
	13200	91	91,3						
	15840	77	88,3						
	7503	95	81,5						
KQSN1200-M12S-1080	12505	81	90	740	1080	3550	DN1000	DN1200	25800 kg
	15006	69	87,1						
	7086	85	79,5						
	11810	72	89,5						
KQSN1200-M12S-1020	14172	61	86,9	740	1020	3150	DN1000	DN1200	24900 kg
	6669	75	80						
	11115	64	88,5						
	13338	54	86,8						
KQSN1200-M12S-960	6315	67	83,3	740	960	2800	DN1000	DN1200	24200 kg
	11115	64	88,5						
	13338	54	86,8						
	6315	67	83,3						
KQSN1200-M12SJ-1140	10505	57	91,3	590	1140	2000	DN1000	DN1200	24000 kg
	12630	49	88,3						
	5982	60	81,5						
	9970	51	90						
KQSN1200-M12SJ-1080	11964	43	87,1	590	1080	1800	DN1000	DN1200	23300 kg
	5649	54	79,5						
	9415	45	89,5						
	11298	38	86,9						
KQSN1200-M12SJ-1020	5316	47	80	590	1020	1600	DN1000	DN1200	20000 kg
	8860	40	88,5						
	10632	34	86,8						
	9104	76	82,5						
KQSN1200-M14-1223	15174	62	91,5	590	1223	3150	DN1000	DN1200	24900 kg
	18209	53	86						
	8740	65	82						
	14567	51	90,5						
KQSN1200-M14-1114	17480	42	85	590	1114	2500	DN1000	DN1200	25200 kg
	8304	59	81,5						
	13840	44	89,5						
	16608	36	84						
KQSN1200-M14-1050	7970	55	80,5	590	1050	2000	DN1000	DN1200	24000 kg
	13283	40	88						
	15940	32	83						
	7739	77	82						
KQSN1200-M14-1008	7739	77	82	590	1008	1800	DN1000	DN1200	23300 kg
	7739	77	82						
	7739	77	82						
	7739	77	82						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN1200-N14-1220	12898	62	90,5	590	1220	2800	DN1000	DN1200	26100 kg
	15477	51	85,5						
KQSN1200-N14-1112	7429	69	81,5	590	1112	2240	DN1000	DN1200	24400 kg
	12382	54	89,5						
KQSN1200-N14-1046	14858	44	84,5	590	1046	1800	DN1000	DN1200	23300 kg
	7132	62	81						
KQSN1200-N14-1006	11887	45	88,5	590	1006	1600	DN1000	DN1200	20000 kg
	14264	37	83,5						
KQSN1200-M14J-1223	6847	56	80	490	1223	1800	DN1000	DN1200	23700 kg
	11411	40	87						
KQSN1200-M14J-1114	13693	31	82,5	490	1114	1400	DN1000	DN1200	20100 kg
	7561	52	82,5						
KQSN1200-M14J-1050	12602	42	90,5	490	1050	1120	DN1000	DN1200	18600 kg
	15122	37	85,5						
KQSN1200-M14J-1008	7259	45	82	490	1008	1000	DN1000	DN1200	18100 kg
	12098	35	89,5						
KQSN1200-N14J-1220	14518	29	84,5	490	1220	1600	DN1000	DN1200	23000 kg
	6896	41	81,5						
KQSN1200-N14J-1112	11494	31	88,5	490	1112	1250	DN1000	DN1200	19500 kg
	13793	25	83,5						
KQSN1200-N14J-1046	6619	38	80,5	490	1046	1000	DN1000	DN1200	18100 kg
	11032	28	87						
KQSN1200-N14J-1006	13238	22	82,5	490	1006	900	DN1000	DN1200	8950 kg
	6427	53	82						
KQSN1200-M17S-1001	10712	42	90	740	1001	3150	DN1000	DN1200	24900 kg
	12854	35	85,5						
KQSN1200-M17S-945	6170	48	81,5	740	945	2500	DN1000	DN1200	21100 kg
	10283	37	89						
KQSN1200-M17S-895	12340	31	84,5	740	895	2240	DN1000	DN1200	20700 kg
	5923	42	81						
KQSN1200-M17S-865	9872	31	88	740	865	2000	DN1000	DN1200	19400 kg
	11846	25	83,5						
KQSN1200-M17SJ-1001	5686	39	80	740	830	1800	DN1000	DN1200	19100 kg
	9477	28	86,5						
KQSN1200-M17SJ-945	11372	22	82,5	590	1001	1600	DN1000	DN1200	20000 kg
	8580	73	83						
KQSN1200-M17SJ-895	14300	62	91	590	945	1250	DN1000	DN1200	9095 kg
	17875	53	87						
KQSN1200-M17SJ-865	8026	66	82	590	895	1120	DN1000	DN1200	8890 kg
	13377	54	90						
KQSN1200-M17SJ-830	16722	43	85	590	830	900	DN1000	DN1200	8430 kg
	7611	61	81						
KQSN1200-M20-1180	12685	49	89	490	1180	1800	DN1000	DN1200	23700 kg
	15857	38	84						
KQSN1200-M20-1133	7335	57	80	490	1133	1600	DN1000	DN1200	23000 kg
	12224	45	88						
KQSN1200-M20-1087	15280	34	83	490	1087	1400	DN1000	DN1200	20100 kg
	7058	54	79						
	11763	42	87						
	14704	31	82						
	6481	50	81						
	11401	39	91						
	14252	31	87,5						
	6399	43	80,5						
	10665	34	90						
	13331	27	87,5						
	6068	38	80						
	10114	31	89,5						
	12642	24	87,5						
	5848	34	79,5						
	9746	29	89						
	12182	23	88						
	5627	31	79						
	9388	27	88						
	11723	20	87						
	9742	36	81						
	16236	31	92						
	19483	27	85						
	9352	33	80						
	15587	28	91						
	18704	24	84						
	8978	31	79,5						
	14963	26	90						

Model	Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN1200-N20-1178	17956	22	83	490	1178	1400	DN1000	DN1200	20100 kg
	8287	34	80						
	13812	28	91						
	16574	24	83,5						
KQSN1200-N20-1131	7955	32	79	490	1131	1250	DN1000	DN1200	19500 kg
	13259	26	90						
	15911	22	82,5						
	7637	29	78						
KQSN1200-N20-1085	12729	24	89	490	1085	1120	DN1000	DN1200	18600 kg
	15275	20	81						
	8449	27	80,5						
	14082	23	91,5						
KQSN1200-M20J-1180	16898	20	84,5	425	1180	1120	DN1000	DN1200	19400 kg
	8111	25	80						
	13519	21	90						
	16223	18	83,5						
KQSN1200-M20J-1133	7787	24	79	425	1133	1000	DN1000	DN1200	18800 kg
	12978	20	89,5						
	15574	16	82,5						
	7188	25	80						
KQSN1200-N20J-1178	11980	21	90,5	425	1178	900	DN1000	DN1200	18000 kg
	14375	18	83						
	6921	24	79						
	11535	20	89,5						
KQSN1200-N20J-1131	13842	16	81	425	1131	800	DN1000	DN1200	17500 kg
	6644	22	77,5						
	11074	18	88,5						
	13289	15	80,5						
KQSN1200-N20J-1085	7396	81	80	425	1085	710	DN1000	DN1200	17000 kg
	12326	18	91						
	14791	16	84						
	7100	19	80						
KQSN1200-M20JJ-1180	11833	16	89,5	372	1180	800	DN1000	DN1200	21000 kg
	14200	14	83						
	6816	18	79						
	11360	15	89						
KQSN1200-M20JJ-1133	13632	13	82	372	1087	630	DN1000	DN1200	20000 kg
	6291	20	80						
	10486	16	90						
	12583	14	82,5						
KQSN1200-M20JJ-1087	6040	18	79	372	1178	630	DN1000	DN1200	20000 kg
	10066	15	89						
	12079	13	81,5						
	5798	17	77						
KQSN1200-N20JJ-1178	9664	14	88	372	1131	560	DN1000	DN1200	19500 kg
	11597	12	80						
	9360	63	86						
	15600	52	91						
KQSN1200-N20JJ-1085	18720	42	87	372	1085	500	DN1000	DN1200	19000 kg
	9096	59	85,5						
	15160	49	90						
	18192	40	87,5						
KQSN1200-M20S-957	8850	56	85	740	957	2800	DN1000	DN1200	24200 kg
	14750	45	89,5						
	17700	36	87,5						
	8580	53	85						
KQSN1200-M20S-930	14300	43	89	740	930	2500	DN1000	DN1200	21100 kg
	17160	34	87						
	8400	51	84,5						
	14000	40	88,5						
KQSN1200-M20S-875	16800	32	86	740	875	2000	DN1000	DN1200	19400 kg
	7500	41	84						
	12500	32	91						
	15000	26	86						
KQSN1200-M20S-850	7350	38	84	590	957	1400	DN1000	DN1200	19600 kg
	12250	30	90						
	14700	26	87,5						
	7200	36	83						
KQSN1200-M20SJ-957	12000	28	89,5	590	930	1250	DN1000	DN1200	9095 kg
	14400	23	86						
	6996	33	83						
	11660	26	89						
KQSN1200-M20SJ-930	13992	22	86,5	590	875	1000	DN1000	DN1200	8620 kg

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN1200-M20SJ-850	6840	32	82,5	590	850	1000	DN1000	DN1200	8620 kg	
	11400	25	88,5							
	13680	20	86							
KQSN1200-M27-998	9611	30	80,5	490	998	1250	DN1200	DN1200	19500 kg	
	16018	22	90,5							
	19222	17	84							
KQSN1200-M27-963	9130	28	80	490	963	1120	DN1200	DN1200	18600 kg	
	15217	20	89							
	18261	15	83							
KQSN1200-M27-918	8765	26	79,5	490	918	1000	DN1200	DN1200	18100 kg	
	14608	18	87,5							
	17530	12	82							
KQSN1200-N27-981	8165	28	80	490	981	900	DN1200	DN1200	8820 kg	
	13608	19	89							
	16330	15	83							
KQSN1200-N27-938	7838	27	79,5	490	938	800	DN1200	DN1200	8610 kg	
	13064	18	87,5							
	15676	13	82							
KQSN1200-N27-908	7525	25	79	490	908	800	DN1200	DN1200	8610 kg	
	12541	16	85,5							
	15049	11	81							
KQSN1200-M27J-998	7208	17	80,5	372	998	500	DN1200	DN1200	6990 kg	
	12014	12	90							
	14416	10	83							
KQSN1200-M27J-963	6848	16	80	372	963	450	DN1200	DN1200	10200 kg	
	11413	11	88,5							
	13695	8	82							
KQSN1200-M27J-918	6574	144	79,5	372	918	400	DN1200	DN1200	10200 kg	
	10956	10	87							
	13148	7	81							
KQSN1200-N27J-981	6124	16	80	372	981	400	DN1200	DN1200	10200 kg	
	10206	11	89,5							
	12247	8	83							
KQSN1200-N27J-938	5878	15	79,5	372	938	355	DN1200	DN1200	10200 kg	
	9798	10	88							
	11757	7	82							
KQSN1200-N27J-908	5664	14	79	372	908	355	DN1200	DN1200	10200 kg	
	9406	9	86							
	11287	6	81							
Tên nhóm: 16										
KQSN1400-M27-1108	13356	28	80	425	1108	1600	DN1400	DN1400	21700 kg	
	22260	19	89,5							
	26712	12	83							
KQSN1400-M27-998	12822	25	79,5	425	998	1250	DN1400	DN1400	19800 kg	
	21370	16	88,5							
	25644	10	82							
KQSN1400-N27-1186	11950	30	80	425	1186	1400	DN1400	DN1400	21000 kg	
	19916	21	90,8							
	23899	13	83							
KQSN1400-N27-1106	11472	28	79	425	1106	1250	DN1400	DN1400	19800 kg	
	19120	18	88							
	22944	12	82							
KQSN1400-N27-996	11013	26	78,5	425	996	1120	DN1400	DN1400	19400 kg	
	18355	16	87							
	22026	9	81							
KQSN1400-N27S-1186	13777	33	81	490	1186	2240	DN1400	DN1400	25400 kg	
	22962	27	89							
	27554	16	84							
KQSN1400-N27S-1106	12848	29	80	490	1106	2000	DN1400	DN1400	24500 kg	
	21413	24	88							
	25969	14	82							
KQSN1400-N27S-996	11570	23	79	490	996	1400	DN1400	DN1400	20100 kg	
	19283	19	86,5							
	23140	12	81							
KQSN1400-M27J-1188	12311	24	80,5	372	1188	1250	DN1400	DN1400	23000 kg	
	20518	17	91							
	24622	12	84							
KQSN1400-M27J-1108	11695	22	80	372	1108	1000	DN1400	DN1400	21300 kg	
	19492	15	89,5							
	23391	9	83							
KQSN1400-M27J-998	11227	19	79,5	372	998	800	DN1400	DN1400	21000 kg	
	18712	12	88							
	22455	8	82							

Model		Lưu lượng (m³/h)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ (kg)
KQSN1400-N27J-1186		10464	23	80	372	1186	1000	DN1400	DN1400	21300 kg
		17440	16	90						
		20928	10	83						
KQSN1400-N27J-1106		10045	22	79,5	372	1106	900	DN1400	DN1400	21200 kg
		16742	14	88,5						
		20091	9	82						
KQSN1400-N27J-996		9644	20	79	372	996	710	DN1200	DN1400	20500 kg
		16073	12	86,5						
		19287	7	81						
Tên nhóm: 17										
KQSN1600-M27-1296		15011	28	80,5	372	1296	1600	DN1600	DN1600	25100 kg
		25018	21	92,5						
		30022	15	84						
KQSN1600-M27-1108		14260	25	80	372	1108	1400	DN1600	DN1600	23400 kg
		23767	18	90						
		28521	13	83						
KQSN1600-M27-998		13690	22	79,5	372	998	1120	DN1600	DN1600	22000 kg
		22816	15	88,5						
		27380	11	82						
KQSN1600-N27-1295		12759	26	80	372	1295	1250	DN1600	DN1600	23000 kg
		21265	19	91,5						
		25518	13	83						
KQSN1600-N27-1106		12249	24	79,5	372	1106	1120	DN1600	DN1600	22000 kg
		20414	16	90						
		24497	11	82						
KQSN1600-N27-996		11759	21	79	372	996	900	DN1600	DN1600	21200 kg
		19598	14	88						
		23517	8	81						
KQSN1600-M27J-1188		12009	18	80,5	298	1188	900	DN1600	DN1600	25100 kg
		20014	13	91,5						
		24017	10	83						
KQSN1600-M27J-1108		11408	16	80	298	1108	800	DN1600	DN1600	23400 kg
		19014	12	90						
		22816	8	82						
KQSN1600-M27J-998		10952	14	79,5	298	998	630	DN1600	DN1600	22000 kg
		18253	10	88,5						
		21904	7	81						
KQSN1600-N27J-1186		10207	16	80	298	1186	710	DN1600	DN1600	23000 kg
		17012	12	91						
		20414	8	83						
KQSN1600-N27J-1106		9779	15	79,5	298	1106	630	DN1600	DN1600	22000 kg
		16332	10	89,5						
		19598	7	82						
KQSN1600-N27J-996		9407	14	79	298	996	500	DN1600	DN1600	21200 kg
		15678	9	87,5						
		18814	5	81						

Ghi chú: Giá liên hệ số 097.451.0188

Thân: Gang HT/Gang QT/Thép đúc/SS304/SS316/SS316L

Trục: Thép 45#/40Cr/SS420 (20Cr13)/SS304

Cánh bơm: Gang HT/Gang QT/Thép đúc/SS304/SS316/SS316L

Phốt: Chèn mềm/Phốt cơ khí

Nhiệt độ chất lỏng: Standard ≤80°C, Special configuration 80–130°C