

Model	Lưu lượng (L/s)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ (kW)	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ
XBD3/5-65(W)	5	30	57,4	2960	151	3	DN65	DN65	/
XBD3.5/5-65(W)	5	35	60,91	2960	159	4	DN65	DN65	/
XBD4/5-65(W)	5	40	51,61	2960	185	5.5	DN65	DN65	/
XBD4.5/5-65(W)	5	45	50,65	2960	190	5.5	DN65	DN65	/
XBD5/5-65(W)	5	50	44,46	2960	197	7.5	DN65	DN65	/
XBD6.5/5-65(W)	5	65	44,97	2960	230	11	DN65	DN65	/
XBD7/5-65(W)	5	70	45,79	2960	233	11	DN65	DN65	/
XBD3/10-80(W)	10	30	65,13	2960	164	5.5	DN80	DN80	/
XBD3.5/10-80(W)	10	35	53,41	2960	169	7.5	DN80	DN80	/
XBD4.5/10-80(W)	10	45	60,99	2960	184	11	DN80	DN80	/
XBD5/10-80(W)	10	50	63	2960	192	11	DN80	DN80	/
XBD6/10-80(W)	10	60	61,19	2960	218	15	DN80	DN80	/
XBD7/10-80(W)	10	70	58	2960	226	15	DN80	DN80	/
XBD7.2/10-80(W)	10	72	59,92	2960	228	15	DN80	DN80	/
XBD7.5/10-80(W)	10	75	55,2	2960	237	18.5	DN80	DN80	/
XBD8/10-80(W)	10	80	56,59	2960	242	18.5	DN80	DN80	/
XBD8.3/10-80(W)	10	83	58,2	2960	245	18.5	DN80	DN80	/
XBD9/10-80(W)	10	90	48	2960	258	22	DN80	DN80	/
XBD10/10-80(W)	10	100	47,76	2960	274	30	DN80	DN80	/
XBD11/10-80(W)	10	110	45,08	2960	284	30	DN80	DN80	/
XBD11.5/10-80(W)	10	115	44,61	2960	289	30	DN80	DN80	/
XBD12/10-80(W)	10	120	42,75	2960	294	37	DN80	DN80	/
XBD3/15-80(W)	15	30	71,95	2960	165	7.5	DN80	DN80	/
XBD3.5/15-80(W)	15	35	73,73	2960	171	11	DN80	DN80	/
XBD4/15-80(W)	15	40	70,19	2960	178	11	DN80	DN80	/
XBD4.2/15-80(W)	15	42	74,78	2960	180	11	DN80	DN80	/
XBD4.5/15-80(W)	15	45	71,76	2960	189	15	DN80	DN80	/
XBD5/15-80(W)	15	50	69,47	2960	195	15	DN80	DN80	/
XBD5.2/15-80(W)	15	52	72,81	2960	197	15	DN80	DN80	/
XBD5.5/15-80(W)	15	55	66,02	2960	210	18.5	DN80	DN80	/
XBD6/15-80(W)	15	60	62,5	2960	221	18.5	DN80	DN80	/
XBD6.5/15-80(W)	15	65	68,11	2960	225	18.5	DN80	DN80	/
XBD7/15-80(W)	15	70	64,03	2960	234	22	DN80	DN80	/
XBD7.5/15-80(W)	15	75	61,76	2960	239	22	DN80	DN80	/
XBD8/15-80(W)	15	80	54,11	2960	252	30	DN80	DN80	/
XBD9/15-80(W)	15	90	54,82	2960	263	30	DN80	DN80	/
XBD11/15-80(W)	15	110	51,92	2960	282	37	DN80	DN80	/
XBD3/20-100(W)	20	30	71	2960	160	11	DN100	DN100	/
XBD3.2/20-100(W)	20	32	71	2960	163	11	DN100	DN100	/
XBD3.5/20-100(W)	20	35	71,62	2960	166	15	DN100	DN100	/
XBD4/20-100(W)	20	40	71,5	2960	181	15	DN100	DN100	/
XBD4.2/20-100(W)	20	42	72,5	2960	185	15	DN100	DN100	/
XBD4.5/20-100(W)-I	20	45	71,5	2960	189	15	DN100	DN100	/
XBD4.5/20-100(W)	20	45	71,5	2960	189	18.5	DN100	DN100	/
XBD5/20-100(W)	20	50	69	2960	198	18.5	DN80	DN100	/
XBD5.2/20-100(W)	20	52	69,3	2960	203	18.5	DN100	DN100	/
XBD5.5/20-100(W)	20	55	58	2960	207	22	DN80	DN100	/
XBD6/20-100(W)	20	60	65	2960	216	22	DN80	DN100	/
XBD7.2/20-100(W)	20	72	63	2960	240	30	DN80	DN100	/
XBD8/20-100(W)	20	80	63	2960	248	30	DN80	DN100	/
XBD8.4/20-100(W)	20	84	63	2960	254	30	DN80	DN100	/
XBD9/20-100(W)	20	90	55	2960	265	37	DN80	DN100	/
XBD10/20-100(W)	20	100	57	2960	283	45	DN80	DN100	/
XBD10.5/20-100(W)	20	105	58	2960	286	45	DN80	DN100	/
XBD11/20-100(W)	20	110	59	2960	290	45	DN80	DN100	/
XBD12/20-100(W)	20	120	56	2960	295	55	DN80	DN100	/
XBD12.5/20-100(W)	20	125	51	2960	300	55	DN80	DN100	/
XBD13/20-100(W)	20	130	52	2960	305	55	DN80	DN100	/
XBD14/20-100(W)	20	140	53	2960	316	75	DN80	DN100	/
XBD15/20-100(W)	20	150	53	2960	325	75	DN80	DN100	/
XBD15.5/20-100(W)	20	155	53	2960	331	75	DN80	DN100	/
XBD16/20-100(W)	20	160	53	2960	333	75	DN80	DN100	/
XBD16.5/20-100(W)	20	165	53	2960	336	75	DN80	DN100	/
XBD3/25-100(W)	25	30	76,8	2960	165	11	DN100	DN100	/
XBD3.7/25-100(W)	25	37	73,94	2960	177	15	DN100	DN100	/
XBD4/25-100(W)	25	40	76	2960	181	18.5	DN100	DN100	/
XBD4.5/25-100(W)	25	45	77	2960	189	18.5	DN100	DN100	/
XBD5/25-100(W)	25	50	73,6	2960	200	22	DN100	DN100	/
XBD5.5/25-100(W)	25	55	66	2960	216	30	DN100	DN100	/
XBD6/25-100(W)	25	60	67	2960	221	30	DN100	DN100	/

Model	Lưu lượng (L/s)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ (kW)	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ
XBD6.6/25-100(W)	25	66	66,5	2960	234	30	DN100	DN100	/
XBD7.5/25-100(W)	25	75	67	2960	247	37	DN100	DN100	/
XBD8/25-100(W)	25	80	67	2960	254	37	DN100	DN100	/
XBD3/30-125(W)	30	30	67	2960	165	15	DN125	DN125	/
XBD3.5/30-125(W)	30	35	67,6	2960	174	18,5	DN125	DN125	/
XBD4/30-125(W)	30	40	64	2960	195	22	DN125	DN125	/
XBD4.5/30-125(W)	30	45	67,6	2960	199	22	DN125	DN125	/
XBD5.5/30-125(W)	30	55	67,8	2960	206	30	DN125	DN125	/
XBD6/30-125(W)	30	60	67,8	2960	213	30	DN125	DN125	/
XBD6.5/30-125(W)	30	65	68,5	2960	220	37	DN125	DN125	/
XBD7/30-125(W)	30	70	69	2960	250	37	DN125	DN125	/
XBD7.5/30-125(W)	30	75	69,8	2960	254	37	DN125	DN125	/
XBD9/30-125(W)	30	90	63	2960	258	55	DN125	DN125	/
XBD9.5/30-125(W)	30	95	66	2960	271	55	DN80	DN125	/
XBD10/30-125(W)	30	100	67	2960	275	55	DN80	DN125	/
XBD11.5/30-125(W)	30	115	59	2960	292	75	DN80	DN125	/
XBD12/30-125(W)	30	120	61	2960	300	75	DN80	DN125	/
XBD13/30-125(W)	30	130	61,9	2960	310	75	DN80	DN125	/
XBD13.5/30-125(W)	30	135	61,9	2960	312	75	DN80	DN125	/
XBD15/30-125(W)	30	150	60	2960	327	90	DN80	DN125	/
XBD17/30-125(W)	30	170	58	2960	345	110	DN80	DN125	/
XBD18/30-125(W)	30	180	59,3	2960	352	110	DN80	DN125	/
XBD20/30-125(W)	30	200	55,8	2960	370	132	DN80	DN125	/
XBD3/35-125(W)	35	30	70,8	2960	168	18,5	DN125	DN125	/
XBD4/35-125(W)	35	40	72,8	2960	187	22	DN125	DN125	/
XBD5/35-125(W)	35	50	66	2960	197	30	DN125	DN125	/
XBD5.4/35-125(W)	35	54	67	2960	207	30	DN125	DN125	/
XBD6/35-125(W)	35	60	68	2960	216	37	DN125	DN125	/
XBD7/35-125(W)	35	70	66	2960	230	45	DN125	DN125	/
XBD7.6/35-125(W)	35	76	67	2960	241	45	DN125	DN125	/
XBD8/35-125(W)	35	80	68	2960	252	55	DN125	DN125	/
XBD8.5/35-125(W)	35	85	69	2960	255	55	DN125	DN125	/
XBD9/35-125(W)	35	90	69,6	2960	257	55	DN125	DN125	/
XBD10/35-125(W)	35	100	58	2960	280	75	DN80	DN125	/
XBD10.5/35-125(W)	35	105	59	2960	285	75	DN80	DN125	/
XBD11/35-125(W)	35	110	60	2960	290	75	DN80	DN125	/
XBD11.5/35-125(W)	35	115	61	2960	295	75	DN80	DN125	/
XBD12/35-125(W)	35	120	62	2960	301	90	DN80	DN125	/
XBD13/35-125(W)	35	130	62	2960	310	90	DN80	DN125	/
XBD14/35-125(W)	35	140	63	2960	317	90	DN80	DN125	/
XBD15/35-125(W)	35	150	65	2960	330	110	DN80	DN125	/
XBD16/35-125(W)	35	160	65,7	2960	340	110	DN80	DN125	/
XBD17/35-125(W)	35	170	58	2960	345	110	DN80	DN125	/
XBD18/35-125(W)	35	180	58	2960	354	132	DN80	DN125	/
XBD19/35-125(W)	35	190	59	2960	360	132	DN80	DN125	/
XBD3/40-125(W)	40	30	74,72	2960	168	18,5	DN125	DN125	/
XBD3.4/40-125(W)	40	34	73,03	2960	176	22	DN125	DN125	/
XBD3.6/40-125(W)	40	36	76,22	2960	178	22	DN125	DN125	/
XBD4/40-125(W)	40	40	79,14	2960	189	30	DN125	DN125	/
XBD4.5/40-125(W)	40	45	77,34	2960	194	30	DN125	DN125	/
XBD5/40-125(W)	40	50	78,06	2960	202	30	DN125	DN125	/
XBD5.5/40-125(W)	40	55	74,25	2960	213	37	DN125	DN125	/
XBD6/40-125(W)	40	60	76,84	2960	218	37	DN125	DN125	/
XBD6.2/40-125(W)	40	62	77,84	2960	220	37	DN125	DN125	/
XBD7/40-125(W)	40	70	70,12	2960	239	45	DN125	DN125	/
XBD7.2/40-125(W)	40	72	71,12	2960	241	45	DN125	DN125	/
XBD8/40-125(W)	40	80	73,79	2960	251	55	DN125	DN125	/
XBD8.5/40-125(W)	40	85	74,22	2960	255	55	DN125	DN125	/
XBD8.7/40-125(W)	40	87	74,72	2960	258	55	DN125	DN125	/
XBD9.5/40-125(W)	40	95	69,21	2960	282	75	DN80	DN125	/
XBD10.2/40-125(W)	40	102	70,21	2960	287	75	DN80	DN125	/
XBD11/40-125(W)	40	110	74,56	2960	296	75	DN80	DN125	/
XBD11.4/40-125(W)	40	114	74,96	2960	298	75	DN80	DN125	/
XBD12/40-125(W)	40	120	69,87	2960	309	90	DN80	DN125	/
XBD12.5/40-125(W)	40	125	69,86	2960	313	90	DN80	DN125	/
XBD13/40-125(W)	40	130	69,64	2960	318	90	DN80	DN125	/
XBD14/40-125(W)	40	140	66,63	2960	323	110	DN80	DN125	/
XBD14.5/40-125(W)	40	145	65,24	2960	327	110	DN80	DN125	/
XBD15/40-125(W)	40	150	66,24	2960	331	110	DN80	DN125	/
XBD15.5/40-125(W)	40	155	66,84	2960	336	110	DN80	DN125	/

Model	Lưu lượng (L/s)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ (kW)	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ
XBD17/40-125(W)	40	170	62,63	2960	349	132	DN80	DN125	/
XBD18/40-125(W)	40	180	64,97	2960	356	132	DN80	DN125	/
XBD20/40-125(W)	40	200	61,6	2960	375	160	DN80	DN125	/
XBD4/45-150(W)	45	40	64	2960	198	30	DN150	DN150	/
XBD4.3/45-150(W)	45	43	67,41	2960	205	30	DN150	DN150	/
XBD4.5/45-150(W)	45	45	67,91	2960	209	37	DN150	DN150	/
XBD5/45-150(W)	45	50	70,75	2960	214	37	DN125	DN150	/
XBD5.3/45-150(W)	45	53	71,05	2960	218	37	DN125	DN150	/
XBD6/45-150(W)	45	60	71,31	2960	231	45	DN125	DN150	/
XBD6.4/45-150(W)	45	64	71,31	2960	234	45	DN150	DN150	/
XBD7.5/45-125(W)	45	75	76,55	2960	245	55	DN125	DN125	/
XBD8/45-125(W)	45	80	77,55	2960	248	55	DN125	DN125	/
XBD8.5/45-150(W)	45	75	67,02	2960	269	75	DN125	DN150	/
XBD9/45-150(W)	45	90	66,24	2960	275	75	DN125	DN150	/
XBD9.5/45-150(W)	45	95	67,75	2960	283	75	DN125	DN150	/
XBD10/45-150(W)	45	100	67,88	2960	288	75	DN125	DN150	/
XBD11/45-150(W)	45	110	64,04	2960	299	90	DN125	DN150	/
XBD13/45-150(W)	45	130	63,1	2960	324	110	DN125	DN150	/
XBD16/45-150(W)	45	160	64,37	2960	358	132	DN125	DN150	/
XBD16.5/45-150(W)	45	165	62,21	2960	368	132	DN125	DN150	/
XBD17/45-150(W)	45	170	65,36	2960	372	160	DN125	DN150	/
XBD18/45-150(W)	45	180	61,86	2960	379	160	DN125	DN150	/
XBD19/45-125(W)	45	190	64,86	2960	372	160	DN80	DN125	/
XBD4.5/50-150(W)	50	45	71,26	2960	211	37	DN150	DN150	/
XBD5/50-150(W)	50	50	72,26	2960	220	37	DN125	DN150	/
XBD5.5/50-150(W)	50	55	74,8	2960	227	45	DN125	DN150	/
XBD6/50-150(W)	50	60	75,8	2960	234	45	DN125	DN150	/
XBD6.5/50-150(W)	50	65	71,61	2960	246	55	DN125	DN150	/
XBD7/50-150(W)	50	70	72,94	2960	250	55	DN125	DN150	/
XBD7.4/50-150(W)	50	74	69,07	2960	256	55	DN125	DN150	/
XBD8/50-150(W)	50	80	70,07	2960	269	75	DN125	DN150	/
XBD8.5/50-150(W)	50	85	68,63	2960	271	75	DN125	DN150	/
XBD9/50-150(W)	50	90	69,63	2960	281	75	DN125	DN150	/
XBD9.5/50-150(W)	50	95	71,67	2960	285	75	DN125	DN150	/
XBD10/50-150(W)	50	100	68,75	2960	293	90	DN125	DN150	/
XBD11/50-150(W)	50	110	69,4	2960	302	90	DN125	DN150	/
XBD12/50-150(W)-I	50	120	70,26	2960	314	110	DN125	DN150	/
XBD12.5/50-150(W)	50	125	68,74	2960	318	110	DN125	DN150	/
XBD13/50-150(W)	50	130	69,18	2960	321	110	DN125	DN150	/
XBD14/50-150(W)	50	140	66,53	2960	343	132	DN125	DN150	/
XBD15/50-150(W)	50	150	67,71	2960	352	132	DN125	DN150	/
XBD16/50-150(W)	50	160	66,07	2960	362	132	DN125	DN150	/
XBD17/50-125(W)	50	170	66,24	2960	358	160	DN80	DN125	/
XBD18.5/50-125(W)	50	185	68,15	2960	369	160	DN80	DN125	/
XBD19/50-125(W)	50	190	69,15	2960	375	185	DN80	DN125	/
XBD20/50-125(W)	50	200	66,85	2960	383	185	DN80	DN125	/
XBD5/55-150(W)	55	50	75,84	2960	222	45	DN125	DN150	/
XBD5.6/55-150(W)	55	56	73,73	2960	232	45	DN150	DN150	/
XBD6/55-150(W)	55	60	74,73	2960	242	55	DN125	DN150	/
XBD6.5/55-150(W)	55	65	74,61	2960	246	55	DN125	DN150	/
XBD7/55-150(W)-I	55	70	76,13	2960	248,5	55	DN125	DN150	/
XBD7/55-150(W)	55	70	72,53	2960	259	75	DN125	DN150	/
XBD7.5/55-150(W)	55	75	71,06	2960	269	75	DN125	DN150	/
XBD8/55-150(W)	55	80	74,04	2960	271	75	DN125	DN150	/
XBD8.5/55-150(W)	55	85	72,7	2960	279	75	DN125	DN150	/
XBD9/55-150(W)	55	90	72,85	2960	283	75	DN125	DN150	/
XBD10/55-150(W)	55	100	71,8	2960	295	90	DN125	DN150	/
XBD10.5/55-150(W)	55	105	70,36	2960	300	90	DN125	DN150	/
XBD11/55-150(W)	55	110	71,36	2960	311	110	DN125	DN150	/
XBD12/55-150(W)	55	120	71,3	2960	321	110	DN125	DN150	/
XBD13/55-150(W)	55	130	70,14	2960	330	132	DN125	DN150	/
XBD14/55-150(W)	55	140	68,79	2960	350	132	DN125	DN150	/
XBD16/55-150(W)	55	160	67,72	2960	370	160	DN125	DN150	/
XBD17/55-150(W)	55	170	64,83	2960	375	160	DN125	DN150	/
XBD6.5/60-150(W)-I	60	65	75,53	2960	246	55	DN125	DN150	/
XBD6.5/60-150(W)	60	65	74,53	2960	250	75	DN125	DN150	/
XBD7/60-150(W)	60	70	73,27	2960	262	75	DN125	DN150	/
XBD7.6/60-150(W)	60	76	73,38	2960	269	75	DN125	DN150	/
XBD8/60-150(W)	60	80	73,63	2960	275	75	DN125	DN150	/
XBD8.5/60-150(W)	60	85	77,41	2960	283	75	DN125	DN150	/

Model	Lưu lượng (L/s)	Cột áp (m)	Hiệu suất (%)	Tốc độ (vòng/phút)	Đường kính ngoài của cánh bơm (mm)	Công suất động cơ (kW)	Đường kính cửa xả	Đường kính cửa hút	Khối lượng động cơ
XBD9/60-150(W)	60	90	74,37	2960	285	75	DN125	DN150	/
XBD9.5/60-150(W)	60	95	70,82	2960	293	90	DN125	DN150	/
XBD10/60-150(W)	60	100	70,82	2960	295	90	DN125	DN150	/
XBD11/60-150(W)	60	110	70,34	2960	311	110	DN125	DN150	/
XBD12/60-150(W)-I	60	120	71,52	2960	318	110	DN125	DN150	/
XBD12/60-150(W)	60	120	69,53	2960	319	132	DN125	DN150	/
XBD13/60-150(W)	60	130	69,94	2960	330	132	DN125	DN150	/
XBD13.3/60-150(W)	60	133	71,99	2960	335	132	DN125	DN150	/
XBD14/60-150(W)	60	140	71,96	2960	352	132	DN125	DN150	/
XBD14.6/60-150(W)	60	146	67,19	2960	358	132	DN125	DN150	/
XBD15/60-150(W)	60	150	68,19	2960	362	160	DN125	DN150	/
XBD16/60-150(W)	60	160	68,59	2960	372	160	DN125	DN150	/
XBD17/60-150(W)	60	170	69,1	2960	383	160	DN125	DN150	/
XBD6/65-200(W)	65	60	74,61	2960	250	75	DN150	DN200	/
XBD7/65-200(W)	65	70	76,61	2960	256	75	DN150	DN200	/
XBD9/65-200(W)	65	90	71,63	2960	279	90	DN150	DN200	/
XBD9.5/65-200(W)	65	95	71,02	2960	289	110	DN150	DN200	/
XBD10/65-200(W)	65	100	72,01	2960	291	110	DN150	DN200	/
XBD11/65-200(W)	65	110	68,87	2960	317	132	DN150	DN200	/
XBD12/65-200(W)	65	120	74,09	2960	327	132	DN150	DN200	/
XBD13/65-200(W)	65	130	76,54	2960	333	132	DN150	DN200	/
XBD14/65-200(W)	65	140	70,12	2960	353	160	DN150	DN200	/
XBD15/65-200(W)	65	150	70,12	2960	362	160	DN150	DN200	/
XBD6/70-200(W)	70	60	77,75	2960	242	75	DN150	DN200	/
XBD6.5/70-200(W)	70	65	76,42	2960	251	75	DN150	DN200	/
XBD7/70-200(W)	70	70	77,35	2960	260	75	DN150	DN200	/
XBD7.5/70-200(W)	70	75	75,28	2960	262	75	DN150	DN200	/
XBD8/70-200(W)	70	80	74,72	2960	270	90	DN150	DN200	/
XBD8.5/70-200(W)	70	85	76,54	2960	274	90	DN150	DN200	/
XBD9/70-200(W)	70	90	73,76	2960	280	90	DN150	DN200	/
XBD9.5/70-200(W)	70	95	74,68	2960	289	110	DN150	DN200	/
XBD10/70-200(W)	70	100	73,56	2960	294	110	DN150	DN200	/
XBD12/70-200(W)	70	120	71,11	2960	317	132	DN150	DN200	/
XBD12.5/70-200(W)	70	125	71,11	2960	325	132	DN150	DN200	/
XBD14/70-200(W)	70	140	71,68	2960	353	160	DN150	DN200	/
XBD16/70-200(W)	70	160	68,23	2960	374	185	DN150	DN200	/
XBD6/75-200(W)	75	60	76,68	2960	245	75	DN150	DN200	/
XBD6.5/75-200(W)	75	65	77,68	2960	250	75	DN150	DN200	/
XBD7/75-200(W)	75	70	77,68	2960	256	90	DN150	DN200	/
XBD7.5/75-200(W)	75	75	75,62	2960	260	90	DN150	DN200	/
XBD8/75-200(W)	75	80	77,23	2960	272	90	DN150	DN200	/
XBD9/75-200(W)	75	90	75,5	2960	286	110	DN150	DN200	/
XBD9.5/75-200(W)	75	95	74,65	2960	289	110	DN150	DN200	/
XBD10.5/75-200(W)	75	105	76,18	2960	302	132	DN150	DN200	/
XBD11/75-200(W)	75	110	73,21	2960	310	132	DN150	DN200	/
XBD11.5/75-200(W)	75	115	73,21	2960	313	132	DN150	DN200	/
XBD6/80-200(W)	80	60	76,47	2960	245	75	DN150	DN200	/
XBD7.5/80-200(W)	80	75	76,34	2960	268	90	DN150	DN200	/
XBD8/80-200(W)	80	80	77,23	2960	272	90	DN150	DN200	/
XBD9/80-200(W)	80	90	74,89	2960	289	110	DN150	DN200	/
XBD9.5/80-200(W)	80	95	76,31	2960	290	110	DN150	DN200	/
XBD9.8/80-200(W)	80	98	75,17	2960	292	110	DN150	DN200	/
XBD10/80-200(W)	80	100	75,17	2960	294	132	DN150	DN200	/
XBD10.5/80-200(W)	80	105	74,98	2960	306	132	DN150	DN200	/
XBD11/80-200(W)	80	110	76,18	2960	310	132	DN150	DN200	/
XBD11.5/80-200(W)	80	115	74,81	2960	315	132	DN150	DN200	/
XBD13/80-200(W)	80	130	73,26	2960	332	160	DN150	DN200	/
XBD13.5/80-200(W)	80	135	72,58	2960	340	160	DN150	DN200	/
XBD14/80-200(W)	80	140	73,58	2960	347	185	DN150	DN200	/
XBD15/80-200(W)	80	150	72,63	2960	358	200	DN150	DN200	/
XBD16/80-200(W)	80	160	71,01	2960	363	200	DN150	DN200	/

Ghi chú: Giá liên hệ số 097.451.0188

Thân: Gang HT/Gang QT, tùy dòng và model

Trục: Thép 45#/SS420 (2Cr13)

Cánh bơm: Gang HT/Gang QT/SS420 (2Cr13)/SS304, tùy cấu hình

Phốt: Phốt cơ khí

Nhiệt độ chất lỏng: ≤80°C